

3. (b) Coring:

Core Number	Interval Cored	Footage Cut	Recovery In Feet	Recovery %
1	1366-1370	4	0	0
2	1370-1394	24	0	0
3	2846-2849	3	2	66
4	3157-3167	10	9½	95
5	4478-4508	30	11	27
6	5316-5323	7	7	100
1-6		78	29.5	37.8

Repositories of Core Material

Centre slab of each core retained at Esso Spotswood Warehouse, Melbourne, Victoria.

Side slabs of each core retained by the Tasmanian Mines Department, Hobart and the Bureau of Mineral Resources, Canberra.

(c) Sidewall Sampling

All sidewall cores by Schlumberger wire line chronological sample taker.

Depth (in feet)	Recovery (in inches)	Depth (in feet)	Recovery (in inches)	Depth (in feet)	Recovery (in inches)
1050	2	3353	1½	4424	1½
1200	2½	3355	1½	4427	1½
1350	2	3362	1½	4535	¾
1360	2	3364	1½	4559	1
1801	1	3366	1½	4677	½
1802	1	3368	1½	4780	1
1804	1	3455	1	4783	¾
1806	1	3637	1½	4787	1½
1807	1	3961	1	4790	1½
1808	1	4017	1½	4793	¾
1809	2	4130	1½	4797	1
1959	2	4132	1½	4895	½
2203	1¾	4134	1½	4898	1
2254	1¾	4136	1½	4902	1½
2345	1½	4138	1½	4905	1
2347	1½	4140	¾	4908	¾
2355	1	4142	1½	4911	1
2385	1½	4144	1½	5012	1½
2522	½	4203	½	5015	1½
2562	¾	4205	1	5017	1½
2605	1	4213	1	5019	¾
2705	1½	4222	1½	5021	½
2747	1½	4227	1	5023	¾
2751	1	4232	1	5025	½
2753	1	4244	1½	5027	½
2775	1½	4273	1	5045	1
2777	1½	4285	1½	5047	N/R
2778	1	4336	1½	5050	N/R
2781	2	4355	1½	5052	N/R
2784	1¾	4367	1	5055	½
2786	1½	4415	1	5066	N/R
2902	¾	4417	1¾	5071	½
3015	½	4419	1½	5226	1
3099	1¾	4421	¾	5244	N/R

(N/R = No Recovery)

The above side wall core residues will be retained by Esso's Spotswood Warehouse, Melbourne, Victoria, although in some cases the preparation of palynological, micro paleontological samples and chemical analyses may destroy the small core sample.