362110

OR-0336 Vol. 2

6d

Schlumberger

ISF/SONIC

COUNTY AUSTRALIA
FIELD or LOCATION WILDCAT
WELL DURROON 1
COMPANY ESSO AUSTRALIA LTD

COMPANY ESSO AUSTRALIA LTD
WELL DURROON 1
FIELD WILDCAT
COUNTY AUSTRALIA STATE TASMANIA
LOCATION LAT: 40° 32'S LONG: 147° 12'E
Other Services: FDC/CNL/GR
Sec. Twp. Rge.

Permanent Datum: MSL, Elev. 0
Log Measured From KB, 32 Ft. Above Perm. Datum
Drilling Measured From KB
Elev.: K.B. 32'
D.F. 31'
G.L. -225'

Date	2 NOV'72			
Run No.	2 5"			
Depth—Driller	6200			
Depth—Logger	6153			
Btm. Log Interval	6146			
Top Log Interval	3007			
Casing—Driller	13 3/8 @ 3005	@	@	@
Casing—Logger	3007			
Bit Size	12 1/4"			
Type Fluid in Hole	LIGNOSULPHONATE			
Dens. | Visc.	10.6 | 44			
pH | Fluid Loss	10.0 | 4.4 ml	ml	ml	ml
Source of Sample	FLOWLINE			
Rm @ Meas. Temp.	1.22 @ 77 °F	@ °F	@ °F	@ °F
Rmf @ Meas. Temp.	0.85 @ 71 °F	@ °F	@ °F	@ °F
Rmc @ Meas. Temp.	1.55 @ 71 °F	@ °F	@ °F	@ °F
Source: Rmf | Rmc	PRESS			
Rm @ BHT	0.64 @ 145 °F	@ °F	@ °F	@ °F
Time Since Circ.	5 HOURS			
Max. Rec. Temp.	145 °F	°F	°F	°F
Equip. | Location	2080 | SAL			
Recorded By	CHAFFE			
Witnessed By	MEBBERSON			

OFFSHORE 15

FOLD HERE The well name, location and borehole reference data were furnished by the customer.

Changes in Mud Type or Additional Samples				Scale Changes			
Date | Sample No.				Type Log	Depth	Scale Up Hole	Scale Down Hole
Depth—Driller							
Type Fluid in Hole							
Dens. | Visc.							
ph | Fluid Loss	ml						
Source of Sample							
Rm @ Meas. Temp.	@ °F	@ °F					
Rmf @ Meas. Temp.	@ °F	@ °F					
Rmc @ Meas. Temp.	@ °F	@ °F					
Source: Rmf | Rmc							
Rm @ BHT	@ °F	@ °F					
Rm @ BHT	@ °F	@ °F					
Rm @ BHT	@ °F	@ °F					

Run No.	2
Ind. Panel No.	48
Mem. Panel No.	53
Ind. Cart. No.	60
Ind. Sonde No.	27
Sonic Panel No.	34
Oscil. Panel No.	
Sonic Cart. No.	32
Sonic Sonde No.	93
G.R. Cart. No.	
G.R. Panel No.	
Caliper No.	
TTR No.	
S.E.	
SBR	1
EX Cent. Device	S.O. PADS
Stand off-Inches	1 1/2"

REMARKS:

Service Order No.-
API Serial No.-
Check one, filling in blanks where applicable:
☒ Surface determined sonde errors used for 6FF40.
☐ 6FF40 sonde error corrected for inch

5 cm

DEPTHS 5"

INTERVAL TRANSIT TIME
MICROSECONDS PER FOOT

T 3 R₁ 2 R₂

140 90 40

SPONTANEOUS-POTENTIAL
millivolts

10
— +

DEPTHS 5"

RESISTIVITY
ohms – m²/m

SFL
0.2 1.0 10 100 1000 2000

6 FF40
INDUCTION
0.2 1.0 10 100 1000 2000