371113

08-0338

Enclosure 8

SCHLUMBERGER

CALIPER

COUNTY AUSTRALIA
FIELD or LOCATION WILDCAT
WELL NANGKERO No. 1
COMPANY HEMATITE PETROLEUM

COMPANY HEMATITE PETROLEUM PTY. LTD.
WELL NANGKERO No. 1
FIELD WILDCAT
COUNTY AUSTRALIA STATE TASMANIA
LOCATION 40° 04' 25.0" S 145° 58' 40.6" E
Other Services: ISF/SONIC/GR
Sec. Twp. Rge.

Permanent Datum: MSL, Elev. 0
Log Measured From KB, 32 Ft. Above Perm. Datum
Drilling Measured From KB
Elev.: K.B. 32'
D.F. 31'
G.L. -261'

Date	27.4.74			
Run No.	ONE			
Depth—Driller	3300			
Depth—Logger	3246			
Btm. Log Interval	3245			
Top Log Interval	645			
Casing—Driller	20" @ 643	@	@	@
Casing—Logger	645			
Bit Size	16.5"			
Type Fluid in Hole	SEA WATER			
Dens. | Visc.	9.3 | 52			
pH | Fluid Loss	8.0 | 8.6 ml	ml	ml	ml
Source of Sample	FLOWLINE			
Rm @ Meas. Temp.	0.29 @ 66 °F	@ °F	@ °F	@ °F
Rmf @ Meas. Temp.	0.23 @ 66 °F	@ °F	@ °F	@ °F
Rmc @ Meas. Temp.	0.93 @ 68 °F	@ °F	@ °F	@ °F
Source: Rmf Rmc	PRES | PRES			
Rm @ BHT	0.18 @ 111 °F	@ °F	@ °F	@ °F
Time Since Circ.	6 HOURS			
Max. Rec. Temp.	110/112 °F	°F	°F	°F
Equip. | Location	2080 | SAL			
Recorded By	HANNINGTON, WADIER			
Witnessed By	HODGSON			

FOLD HERE The well name, location and borehole reference data were furnished by the customer.

REMARKS

Changes in Mud Type or Additional Samples		
Date | Sample No.		
Depth—Driller		
Type Fluid in Hole		
Dens. | Visc.		
ph . | Fluid Loss	ml	ml
Source of Sample		
Rm @ Meas. Temp.	@ °F	@ °F
Rmf @ Meas. Temp.	@ °F	@ °F
Rmc @ Meas. Temp.	@ °F	@ °F
Source: Rmf | Rmc		
Rm @ BHT	@ °F	@ °F
Rmf @ BHT	@ °F	@ °F
Rmc @ BHT	@ °F	@ °F

Scale Changes

Type Log	Depth	Scale Up Hole	Scale Down Hole

Equipment Data

Run No.	Tool Type	Pad Type	Tool Pos.	Other
ONE	PGT	DENS.		

5 cm

CALIBRATION DATA

5 cm

COMPANY HEMATITE PETROLEUM PTY. LTD.
WELL NANGKERO No. 1
FIELD WILDCAT
COUNTY AUSTRALIA STATE TASMANIA

SCHL. FR 3245'
SCHL. TD 3246'
DRLR TD 3300'
Elev:
KB 32'
DF 31'
GL -261'