374120

OK-0838

Schlumberger

PICKER AXIS
WITH CONTINUOUS DIP

CONTINUOUS DIPMETER

(CONTINUOUS DIP METER)

COUNTRY	AUSTRALIA
FIELD or LOCATION	WILDCAT
WELL	AR00-1
COMPANY	HEMATITE PETROLE

COMPANY	HEMATITE PETROLEUM PTY.LTD
WELL	AR00-1
FIELD	WILDCAT
COUNTRY	AUSTRALIA
STATE	TASMANIA
TYPE OF PLOT	Polar / Stereo

Permanent Datum	MSL	Elev.	
Log Measured From	KB	12 Ft Above Perm. Datum	Elev. Kb 26.2,2.75
Drilling Measured From	KB		

Run No.		One	Three
Depth - Driller		9690	9696
Depth - Logger		9696	9696
Top Log Interval		7360	6930
Bottom Log Interval		9690	9690
Casing - Driller	13 3/8 @ 273	13 3/8 @ 273	13 3/8 @ 273
Casing - Logger			
Bit Size	12 1/4	12 1/4	12 1/4
Type Fluid in Hole	SALT WATER	SALT WATER	SALT WATER
Dens. / Visc.	9.4 / 40	9.4 / 40	9.4 / 40
PH / Fluid Loss	9.5 / 4.8	9.5 / 4.8	9.5 / 4.8
Source of Sample	FLOWLINE	FLOWLINE	FLOWLINE
Rm @ Measured Temp.	0.160 @ 68°F	0.160 @ 68°F	0.160 @ 68°F
Rmf @ Measured Temp.	0.120 @ 68°F	0.120 @ 68°F	0.120 @ 68°F
Rmc @ Measured Temp.	0.080 @ 68°F	0.080 @ 68°F	0.080 @ 68°F
Source: Rmf / Rmc	MEASURED / MEASURED	MEASURED / MEASURED	MEASURED / MEASURED
Rm @ BHT	0.160 @ 215°F	0.160 @ 215°F	0.160 @ 215°F
Time Since Circulation	15 HRS	15 HRS	15 HRS
Max. Rec. Temp.	215°F	215°F	215°F
Equipment Location	CAMS	CAMS	CAMS
Recorded By	GOLDSTEIN	GOLDSTEIN	GOLDSTEIN
Witnessed By	MR. SCOTT	MR. SCOTT	MR. SCOTT

DIGITAL RECORDING

5 cm

CORRELATION CURVE	DEPTHS	TRUE DIP ANGLE AND DIRECTION 10° 20° 30° 40° 50° 60° 70° 80° 90°	SHIFT & DIRECTION OF SENSE

CORRELATION CURVE — DEPTHS — DIP ANGLE AND DIRECTION — MINIMUM SHIFT

12 FT X 9 FT 20 DEG X 1

REFERENCE 4540.00

STANDARD PLOT INCLUDING ALL RESULTS

ZONE FROM 7360 TO 9690

RESISTIVITY INCREASES

7400 7500 7600 7700 7800 7900 8000 8100 8200 8300 8400 8500 8600 8700 8800 8900 9000 9100 9200 9300 9400 9500 9600 9700

5 cm