





GAMMA RAY
CALIPER
NEUTRON POROSITY INDEX %
BULK DENSITY
CALIBRATION DATA
CALIBRATION DATA





GAMMA RAY
CALIPER
NEUTRON POROSITY WHITE %
BULK DENSITY
CORRECTION
CALIBRATION DATA




NEUTRON POROSITY INDEX %
GAMMA RAY
CALIPER
BULK DENSITY
CORRECTION
CALIBRATION DATA


CALIBRATION SPECTRUM
CALIBRATION DECAY SURVEY


CALIBRATION DECAY SURVEY


CALIBRATION DATA

OFFSHORE

PUBLIC INSPECTION

DEPARTMENT OF PRIMARY INDUSTRIES AND ENERGY

PETROLEUM SAFETY

SEP 1995

RECEIVED

Document Data Processing Pty Limited

105

ENCLOSURE 1(a) 343119 OP. 340

SCHLUMBERGER

BOREHOLE COMPENSATED SONIC LOG

COUNTY AUSTRALIA
FIELD or LOCATION WILDCAT
WELL NARIMBA 1

COMPANY ESSO AUSTRALIA

COMPANY ESSO AUSTRALIA
WELL NARIMBA 1
FIELD WILDCAT
COUNTY AUSTRALIA STATE TASMANIA
LOCATION Lat: 40° 16' 16.159" S
Long: 145° 43' 53.327" E
Sec. Twp. Rge.

Permanent Datum: MSL Elev.: 0
Log Measured From KB 32 Ft. Above Perm. Datum
Drilling Measured From KB

Elev.: K.B. 32
D.F. 31
G.L. -253

Other Services: ISF, HDT FDC/CNL/GR ST

Date	1 OCT 73
Run No.	FIVE
Depth—Driller	11003
Depth—Logger	10993
Btm. Log Interval	10982
Top Log Interval	10200
Casing—Driller	9 5/8 @ 10008
Casing—Logger	8709
Bit Size	8½
Type Fluid in Hole	LIGNOSULFONATE
Dens. / Visc.	11.0 / 44
pH / Fluid Loss	9.8 / 4 ml
Source of Sample	FLOWLINE
R_m @ Meas. Temp.	0.80 @ 69 °F
R_{mf} @ Meas. Temp.	0.56 @ 68 °F
R_{mc} @ Meas. Temp.	1.1 @ 68 °F
Source: R_{mf} / R_{mc}	Pumped / Pumped
R_m @ BHT	0.21 @ 266 °F
Time Since Circ.	9¾ HRS
Max. Rec. Temp.	266/266 °F
Equip. Location	COFFS/LAUNCESTON
Recorded By	SVALBE
Witnessed By	CROWTHER/CLARKE

FOLD HERE — The well name, location and borehole reference data were furnished by the customer.

REMARKS

Changes in Mud Type or Additional Samples

Date	Sample No.		
Depth—Driller			
Type Fluid in Hole			
Dens. / Visc.			
ph / Fluid Loss		ml	
Source of Sample			
R_m @ Meas. Temp.	@ °F	@ °F	
R_{mf} @ Meas. Temp.	@ °F	@ °F	
R_{mc} @ Meas. Temp.	@ °F	@ °F	
Source: R_{mf} / R_{mc}			
R_m @ BHT	@ °F	@ °F	
R_{mf} @ BHT	@ °F	@ °F	
R_{mc} @ BHT	@ °F	@ °F	

Scale Changes

Type Log	Depth	Scale Up Hole	Scale Down Hole

Equipment Data

Run No.	Tool Type	Pad Type	Tool Pos.	Other
FIVE	SLT-L		ECCEN	

C.D.: FADS S.O.:
Equip. Used: CART. No. SLC-OG 32
PANEL No. SLP-JG 34 SL0-8 599
SONDE No. SLS-KB 93

CALIBRATION:	BACKGND. CPS.	SOURCE CPS.	GALV. INCR. DIVISIONS	SENS. TAP (FOR CAL.)	SENS. TAP (RECORD)	TIME CONST.	RECORDING SPEED (FT./MIN.)
GAMMA RAY:							

$$\text{Velocity (feet per second)} = \frac{1{,}000{,}000}{\text{Interval Transit Time (microseconds per foot)}}$$

5 cm

DEPTHS

INTERVAL TRANSIT TIME
MICROSECONDS PER FOOT

2"

T 3 R1 2 R2

140 90 40

10200
10300
10400
10500
10600
10700
10800
10900
11000

T 3 R1 2 R1

2"

140 90 40

DEPTHS

INTERVAL TRANSIT TIME
MICROSECONDS PER FOOT

COMPANY ESSO AUSTRALIA LTD
WELL NARIMBA 1
FIELD WILDCAT
COUNTY AUSTRALIA STATE TASMANIA

SCHL. FR 10982
SCHL. TD 10993
DRLR TD 11003
Elev:
KB 32
DF 31
GL -253

5 cm

| | | |

