

DEPTHS	%	DESCRIPTION
8813-8820	20	<u>Sandstone</u> , white, fine grained, consolidated, with few unconsolidated coarse grains.
	20	<u>Siltstone</u> , white, moderately firm, trace carbonaceous laminae.
	60	<u>Shale</u> with trace coal
8820-8830	10	<u>Sandstone</u>
	30	<u>Siltstone</u> , laminated, with carbonaceous streaks
	60	<u>Shale</u> , brown, firm, slightly silty, finely micaceous
8830-8840	10	<u>Sandstone</u> as above
	10	<u>Siltstone</u> as above
	80	<u>Shale</u>
8840-8850	10	<u>Sandstone</u>
	20	<u>Siltstone</u> , trace pyrite
	70	<u>Shale</u> , trace fossil.
		POH to run casing Ran 9-5/8" casing with shoe at 8808'. Cemented with 374 Sx. Ran Seal assembly. Drilled out plug @ 530. Pressure checked 16.5# at 8861.
8850-8860	100	<u>Cement</u> cavings
8860-8870	30	<u>Cement</u> cavings
	20	<u>Siltstone</u> as above
	50	<u>Shale</u> as above
8870-8880	50	<u>Cement</u> cavings
	10	<u>Siltstone</u>
	40	<u>Shale</u>
8880-8890	30	<u>Cement</u>
	20	<u>Siltstone</u> as above with trace unconsolidated fine grained, subangular quartz
	50	<u>Shale</u> , brown, carbonaceous, silty, finely micaceous with trace fossil.
8890-8900	10	<u>Siltstone</u>
	10	<u>Shale</u>
	80	<u>Coal</u> , black, brittle.
8900-8910	20	<u>Siltstone</u> , white with very fine grained sand, firm, thin bedded.
	70	<u>Shale</u>
	10	<u>Coal</u>
8910-8920	20	<u>Siltstone</u>
	80	<u>Shale</u> , brown, silty, firm, carbonaceous, finely micaceous, trace coal.
8920-8930	40	<u>Siltstone</u> , white to tan white with some very fine grained sand, very hard indurated, slightly carbonaceous
	60	<u>Shale</u> , as above, trace fossil.
8930-8940	20	<u>Sandstone</u> , white, very fine to fine grained quartz, very silty, hard, tight.
	30	<u>Siltstone</u> as above
	50	<u>Shale</u> as above <u>Ironstone</u> ?
8975		PO to CB
8940-8950	10	<u>Siltstone</u>
	90	<u>Shale</u>
8950-8960	90	<u>Siltstone</u> , tan to buff, moderately firm, argillaceous
	10	<u>Shale</u>