

IV CASING - LINER - TUBING RECORD							
Type	Size	Weight	Grade	Thread	No. Joints	Amount	Depth
20"/30"	Pile Joint						
	20"	91.5	X-52	CIW CC Connector CIW Threaded Conn. box and pin	10	429	
				Rotary Bushing to 16-3/4" casing		291	720
	13-3/8"	72	C-75	Butt.	69	2738	
				Rotary Bushing to 13-3/8" casing housing		294	3032
	9-5/8"	47	N-80	Butt.	218	8469	
				Rotary Bushing to 9-5/8" casing housing		292	8761

V CEMENT RECORD				
String	20"/30" Pile Jt.	20" casing	13-3/8" casing	9-5/8" casing
Type of Cement	43 sx Aust. 'N' 2% CaCl ₂	785 sx Aust. 'N'+ 6% Gel	810 sx Aust. 'N' 135 sx Aust. 'N' + 1% CaCl ₂	500 sx Aust. 'N' + 1.2% HR-12
Number of FT ³	51	1740	1115	590
Average weight of slurry	16.0 ppg	13.7/15/6 ppg	15.6 ppg	15.6 ppg
Cement Top	-	Surface	1500' Calculated	7000' Calculated
Casing Tested with	-	500 psi	1000 psi	3000 psi
Number of Centralizers	-	6	10	12 _t
Number of Scratchers	-	-	-	-
Stage Collar etc.	-	-	-	-
Remarks	-	350 sx Aust. 'N'+ 2% CaCl ₂ Tail Slurry		

B A S I C