

OFFSHORE 13

ESSO AUSTRALIA LTD.
SIDEWALL CORE DESCRIPTIONS

WELL POONBOON-1
GEOLOGIST A.J. Mebberson
SERVICE CO Schlumberger

PAGE 1 OF 2
ATT 30 REC 30

IES RUN NO 1 SWC RUN NO 1 DATE 14/9/72

NO. 1a	DEPTH 1	REC 2	ROCK TYPE 3	MODIFIERS 4	CAL 5	COLOR 6	INDUR DEG 7	GRAIN SIZE 8	SRTG 9	RND 10	DISS CLAY 11	STAIN 12	FLOURESCENCE				CUT FLUOR.		CUT RESIDUE		SHOW 21	PROB PROD 22	REMARKS - GAS 23
													% RK	DISTR 14	INTEN 15	COLOR 16	INTEN 17	COLOR 18	QUAN 19	COLOR 20			
1	8788	3/4	shale	Carb., silty	sl.	grey	soft	-	-	-													Laminated
2	8700	3/4	siltst		sl.	wh.gy	soft																Laminated
3	8610	3/8	shale	siltysl. carb	sl.	gy-wh	firm																
4	8500	1/2	siltst		-	gy-wh	friable																
5	8400	3/4	siltst	carb.sl.shly-	gy-wh	friable																	Laminated
6	8300	3/4	shale	sl.carb.	-	gy.	soft																
7	8250	3/8	siltst	sl.sandy	-	wh.	firm																Shale Laminae
8	8200	5/8	siltst	sl.carb.	-	wh.gy.	fri.																
9	8114	3/4	sh. siltst		-	wh.gy	fri																Laminated
10	8000	3/4	siltst	sl.carb.	-	gy.	fri/fm																
11	7960	1/2	siltst	sl. carb.	-	gy.	fri/fm																
12	7898	1 1/2	siltst	-	-	pl.bn.	friable																
13	7800	1	siltst	carb.	-	gy-wh	fri.																Laminated
14	7706	7/8	siltst	sl.sandy,carb	-	lt.gy	fri.																
15	7602	7/8	siltst	sl.sandycarb.	-	gy-wh	fri.																Laminated
16	7504	1 1/2	siltst.	carb.shaley	-	bn-wh	fri.																Laminated
17	7406	1 1/2	shale		-	black	fiss.																
18	7340	1 1/2	slst.		-	gy-bn wh.	fri.																Laminated
19	7300	1 3/8	shale	v.carb.tr.coal	gy-blk	soft- fiss																	
20	7200	5/8	shale		-	gyblk	fiss																
21	7118	1 1/2	shale	sl. carb.	-	gy bn	fiss. -fm.																
22	7004	3/4	sh/sltst	sl.carb.	-	gy/lt. gy	fiss. -fm.																
23	6908	1"	siltst.	v. sandy	-	wh.	fri																
24	6800	1"	siltst.	-	-	gy/wh	fri																
25	6718	1"	siltst.	-	-	gy-wh	fri																Laminated
26	6600	1"	siltst.	sl. carb.	-	brn.	fri.																
27	6500	1 1/2	sh. siltst.	banded	-	dk.bn. gy-wh	fri																Laminated
28	6418	1 1/2	shale	silty	-	gy-gn	fri																Laminated

ESSO
 BASIC DATA