ENCLOSURE 14b

349068

OR-342

COUNTY AUSTRALIA
FIELD or LOCATION WILDCAT
WELL POONBOON 1

COMPANY ESSO AUSTRALIA

SCHLUMBERGER INDUCTION-ELECTRICAL LOG

COMPANY ESSO AUSTRALIA LIMITED
WELL POONBOON 1
FIELD WILDCAT
COUNTY AUSTRALIA STATE TASMANIA
LOCATION LAT. 40° 08'S LONG. 145° 55'E
Other Services: FDC/GR
Sec. ____ Twp. ____ Rge. ____

Permanent Datum: MSL, Elev. 0
Log Measured From KB, 32 Ft. Above Perm. Datum
Drilling Measured From KB
Elev.: K.B. 32 D.F. 31 G.L. -259

Date	26 SEP'72		
Run No.	2 5"		
Depth—Driller	10,493		
Depth—Logger	10,500		
Btm. Log Interval	10,499		
Top Log Interval	8,763		
Casing—Driller	9 5/8" @ 8761	@	@
Casing—Logger	8763		
Bit Size	8 1/2"		
Type Fluid in Hole	LIGNOSULPHONATE		
Dens. | Visc.	11.1 | 44		
pH | Fluid Loss	9.8 | 5.2 ml	ml	ml
Source of Sample	CIRCULATION		
R_m @ Meas. Temp.	1.40 @ 61 °F	@ °F	@ °F
R_{mf} @ Meas. Temp.	.074 @ 61 °F	@ °F	@ °F
R_{mc} @ Meas. Temp.	1.57 @ 61 °F	@ °F	@ °F
Source: R_{mf} R_{mc}	PRESS PRESS		
R_m @ BHT	.280 @ 222°F	@ °F	@ °F
Time Since Circ.	6 HOURS		
Max. Rec. Temp.	222/223.5°F	°F	°F
Equip. | Location	2080 | SAL		
Recorded By	SEVELY		
Witnessed By	McKAY		

FOLD HERE The well name, location and borehole reference data were furnished by the customer.

REMARKS

Changes in Mud Type or Additional Samples		
Date | Sample No.		
Depth—Driller		
Type Fluid in Hole		
Dens. | Visc.		
ph | Fluid Loss	ml	
Source of Sample		
R_m @ Meas. Temp.	@ °F	@ °F
R_{mf} @ Meas. Temp.	@ °F	@ °F
R_{mc} @ Meas. Temp.	@ °F	@ °F
Source: R_{mf} R_{mc}		
R_m @ BHT	@ °F	@ °F
R_{mf} @ BHT	@ °F	@ °F
R_{mc} @ BHT	@ °F	@ °F

Scale Changes

Type Log	Depth	Scale Up Hole	Scale Down Hole

Equipment Data

Run No.	Tool Type	Tool Position	Other

Run No.: TWO
C.D.: NONE
S.O.: 1 1/2"
Equip. PANEL No.: IRP-L-754
Used: CART. No.: IRC-F-708
SONDE No.: IRS-M-944
IAP No.: MMP2B-378
S.B.R.: 1

Check one, filling in blanks where applicable:
☒ Surface determined sonde errors used for 6FF40.
☐ 6FF40 sonde error corrected for ____ inch borehole signal at Rm =
☐ 6FF40 zero set in hole at depth of ____ feet.

SPONTANEOUS POTENTIAL millivolts	DEPTHS	RESISTIVITY ohms-m²/m	CONDUCTIVITY millimhos/m = 1000/ohms-m²/m
10		A-16"-M SHORT NORMAL 0 — 20 0 — 200	6FF40 INDUCTION 2000 — 0
		INDUCTION 0 — 20 0 — 200	
		AMP. SHORT NORMAL 0 — 4	

SPONTANEOUS-POTENTIAL millivolts	DEPTHS	RESISTIVITY ohms-m²/m	CONDUCTIVITY millimhos/m = 1000/ohms-m²/m
10		AMP. SHORT NORMAL 0 — 4	
		A-16"-M SHORT NORMAL 0 — 20 0 — 200	6 FF40 INDUCTION 2000 — 0
		INDUCTION 0 — 20 0 — 200	

COMPANY ESSO AUSTRALIA LIMITED
WELL POONBOON 1
FIELD WILDCAT
COUNTY AUSTRALIA STATE TASMANIA

SCHL. FR 10,499
SCHL. TD 10,500
DRLR TD 10,493
Elev:
KB 32
DF 31
GL -259

CALIBRATION DATA

REPEAT SECTION



CALIBRATION DATA

COMPANY ESSO AUSTRALIA LIMITED
WELL POONBOON 1
FIELD WILDCAT
COUNTY AUSTRALIA STATE TASMANIA

SCHL. FR 10,499
SCHL. TD 10,500
DRLR TD 10,493
Elev:
KB 32
DF 31
GL -259