

351078

ESSO STANDARD OIL (AUSTRALIA) LTD.

CORE DESCRIPTION

Core No. 2

Note: Core No. 1 3621-3623 No Recovery

WELL: PRAWN A-1

Interval Cored 3938-57 ft., Cut 19 ft., Recovered 3 ft., (15.8%) Fr.

Bit Type C-14A, Bit Size 7 3/4" in., Desc. by C. K. LUNT Date 9th Feb., 1968.
R. L. Graham

Depth & Coring Rate (min./ft.)	Graphic (1" = 5')	Shows	Interval (ft.)	Descriptive Lithology
<p>0 2 4 6 8 10</p>	<p>..... m. q. m. m. q. m. m. q. m. m. q. m.</p>		<p>3938-3938.5 (0.5') SAND: lt. brn. (indiv. sand grs. are tan to milky to clr; silty to m. gr. with occ. crs. gr.; fair sorting; unconsol.; sl. calc.; w/ traces of minute carbon mat'l.</p> <p>3938.5-3941 (2.5') SANDY SILTSTONE: dk. brn-black; m. hd; w/ abund. v.f.-med. qtz sand grains (+ siderite?). Occ. isolated lumps of py. (up to 2 cm.) Tr. fossil frags.</p>	

REMARKS:

