

IV		CASING-LINER-TUBING RECORD					
Type	Size	Weight	Grade	Thread	No. Joints	Amount	Depth
KB ELEVATION ABOVE CASING HEAD						300.00	300.00
30"/20" PILE JOINT						33.50	333.50
	20"	129.32#	J-55	JV	10 + Float Shoe	404.12	737.62
KB ELEVATION ABOVE HANGER						300.00	300.00
	13-3/8"	54.5#	J-55	Butt	63 + Hanger & Float Collar	2607.18	2907.18
	13-3/8"	54.5#	J-55	Butt	1 + Float Shoe	41.58	2948.76
PILE JOINT AND WELLHEAD RECOVERED.							

V		CEMENT RECORD		
String	20"/30" PILE JOINT	20"	13-3/8"	
Type of Cement	55 sx Aust N + 2% CaCl <sub>2</sub>	1100 sx Aust N followed by 350 sx Aust N + 2% CaCl <sub>2</sub>	800 sx Aust N	
Number of FT <sup>3</sup>	65	1711	944	
Average Weight of Slurry	15.6 ppg	15.6 ppg	15.6 ppg	
Cement Top		Sea floor	1300' calc.	
Casing Tested with			1500 psi	
Number of Centralizers		6	10	
Number of Scratchers				
Stage Collar, etc.				
Remarks			Plug did not bump	