OR 349 B

Schlumberger

DIL-BHC-CAL-GR 1:240 873-94M

5 cm

CSU Field Log

ENCLOSURE 11a

Digitize ~~SFL~~ ILM

380082

COMPANY:	HEMATITE PETROLEUM LTD.	OTHER SERVICES-
WELL:	PIPIPA 1	
FIELD:	BASS BASIN	
SUITE:	SUITE 1 RUN 1	
STATE:	VICTORIA	
NATION:	AUSTRALIA	
LOCATION:	BASS STRAIT	

SEC: TWP: RGE:

LATITUDE: 40 23 11.26S

LONGITUDE: 145 41 44.96E

PERMANENT DATUM: MSL

ELEV. OF PERM. DATUM:

LOG MEASURED FROM: DF

20.7 M ABOVE PERM. DATUM

DRLG. MEASURED FROM: DF

ELEVATIONS-

KB: 21.0 M

DF: 20.7 M

GL: -73.0 M

PROGRAM TAPE NO: 20.1A

DATE: 8 MAY 1982

RUN NO: 1

DEPTH-DRILLER:	880.0 M
DEPTH-LOGGER:	875.0 M
BTM. LOG INTERVAL:	873.0 M
TOP LOG INTERVAL:	94.0 M
CASING-DRILLER:	213 M
CASING-LOGGER:	213 M
CASING:	20
WEIGHT:	94.00 LB/F
BIT SIZE:	17 1/2
DEPTH:	880 M

TYPE FLUID IN HOLE:	SEAWATER GEL
DENSITY:	9.1 LB/G
VISCOSITY:	35.0 S
PH:	7.0
FLUID LOSS:	NOT CONTROLLED
SOURCE OF SAMPLE:	FLOWLINE
RM:	0.370 OHM AT 14.4 DC
RMF:	0.315 OHM AT 13.3 DC
RMC:	0.542 OHM AT 12.2 DC
SOURCE RMF/RMC:	PRESS/PRESS
RM AT BHT:	0.218 OHM AT 39.4 DC
RMF AT BHT:	0.180 OHM AT 39.4 DC
RMC AT BHT:	0.300 OHM AT 39.4 DC
TIME CIRC. STOPPED:	0300/8
TIME LOGGER ON BTM.:	0930/8
MAX. REC. TEMP:	39.4 DC
LOGGING UNIT NO:	500
LOGGING UNIT LOC:	S. CROSS
RECORDED BY:	M. AW
WITNESSED BY:	M. SMITH M. HEWKES

REMARKS:

1.5 INCH STANDOFF USED ON INDUCTION
SP NOISY-UNKNOWN CAUSE

EQUIPMENT NUMBERS-

DIS 1092	DIC 1655	SLS RC 741	SLC K 741
SGC JAA 1537	NSM 973	SLM DA 1040	IEM BC 946

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

FILE

101

AFTER SURVEY TOOL CHECK SUMMARY

PERFORMED: 82/05/08
PROGRAM FILE: ISON (VERSION 20.1A 79/07/07)

DITD TOOL CHECK

	ZERO		PLUS		
	BEFORE	AFTER	BEFORE	AFTER	UNITS
ILD	0.0	-1.2	499.8	496.6	MMHO
SFL	0.0	-1.9	500.0	501.9	MMHO

ILD SONDE ERROR CORRECTION : 6.2 MMHO
ILM SONDE ERROR CORRECTION : 7.8 MMHO

FILE

8

BS (IN)	
10.00	20.00
CALI(IN)	
10.00	20.00
GR (GAPI)	
0.0	150.0
SP (MV)	
-80.00	20.00

*DT (US/M)	
900.0	100.0
ILD (OHMM)	
0.2000	2000.
SFLA(OHMM)	
0.2000	2000.

FILE

5

FILE

5

BS (IN)	
10.00	20.00
CALI(IN)	
10.00	20.00
GR (GAPI)	
0.0	150.0
SP (MV)	
-80.00	20.00

*DT (US/M)	
900.0	100.0
ILD (OHMM)	
0.2000	2000.
SFLA(OHMM)	
0.2000	2000.

SENSOR MEASURE POINT TO TENSION REFERENCE POINT

AMPL	10.5	METER	DT	9.8	METER
SRAT	9.8	METER	CBL	10.5	METER
GR	22.5	METER	TT	10.5	METER
ILD	2.1	METER	CALI	16.6	METER
ILM	1.0	METER	SFL	1.2	METER
SPAR	.0	METER	SP	.0	METER
CMSF	16.5	METER	TENS	.0	METER
NOIS	8.0	METER	I1	16.6	METER

PARAMETERS

NAME	VALUE	UNIT	NAME	VALUE	UNIT
CDTS	100.0		BS	17.50	IN
DTF	189.0	US/F	DTM	56.00	US/F
SBR	1.000	OHMM	DSEC	6.200	MMHO
SPT	STAN		MSEC	7.800	MMHO
DO	0.0		BHS	OPEN	

BS (IN)	
10.00	20.00
CALI(IN)	
10.00	20.00
GR (GAPI)	
0.0	150.0
SP (MV)	
-80.00	20.00

*DT (US/M)	
900.0	100.0
ILD (OHMM)	
0.2000	2000.
SFLA(OHMM)	
0.2000	2000.

FILE

REPEAT SECTION