OR 349B

Schlumberger

HDT 1:240 2110-1400M

CSU Field Log

ENCLOSURE 13

COMPANY: HEMATITE PETROLEUM PTY. LTD.

380086

WELL: PIPIPA 1

FIELD: WILDCAT
SUITE: SUITE 2 RUN 1
STATE: TASMANIA
NATION: AUSTRALIA
LOCATION: BASS BASIN

SEC: TWP: RGE:
LATITUDE: 40 23 11.26S
LONGITUDE: 145 41 44.96E

PERMANENT DATUM: MSL
ELEV. OF PERM. DATUM:
LOG MEASURED FROM: DF
20.7 M ABOVE PERM. DATUM
DRLG. MEASURED FROM: DF

ELEVATIONS-
KB: 21.0 M
DF: 20.7 M
GL: -73.0 M

OTHER SERVICES-
DIL-BHC-MSFL
LDL-CNL-GR
CST
CIS-S

PROGRAM TAPE NO:
20.2

DATE: 17 MAY 1982
RUN NO: 1

DEPTH-DRILLER: 2115.0 M
DEPTH-LOGGER: 2115.0 M
BTM. LOG INTERVAL: 2110.0 M
TOP LOG INTERVAL: 1400.0 M

CASING-DRILLER:	213 M	866 M
CASING-LOGGER:	213 M	866 M
CASING:	20	13 3/8
WEIGHT:	94.00 LB/F	45.00 LB/F
BIT SIZE:	17 1/2	12 1/4
DEPTH:	880 M	2115 M

TYPE FLUID IN HOLE: SEAWATER POLYMER
DENSITY: 10.0 LB/G
VISCOSITY: 47.0 S
PH: 10.6
FLUID LOSS: 6.8 C3
SOURCE OF SAMPLE: FLOWLINE
RM: 0.302 OHMM AT 18.3 DC
RMF: 0.212 OHMM AT 15.5 DC
RMC: 0.412 OHMM AT 16.6 DC
SOURCE RMF/RMC: PRESS/PRESS
RM AT BHT: 0.112 OHM AT 86.1 DC
RMF AT BHT: 0.073 OHM AT 86.1 DC
RMC AT BHT: 0.146 OHM AT 86.1 DC

TIME CIRC. STOPPED: 2330/16
TIME LOGGER ON BTM.: 1715/17

MAX. REC. TEMP: 86.1 DC

LOGGING UNIT NO: 500
LOGGING UNIT LOC: S. CROSS
RECORDED BY: M. AW
WITNESSED BY: R.TOLLIDAY

REMARKS:

CAL 1 SPIKING IN FEW PLACES DUE TO STICKY POT.

EQUIPMENT NUMBERS-

HDE-CB 995 HDM-F 916 HDS-D 793 DAM-A 2730

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

FILE
101

DEVI(DEG)
-1.000 9.000
RB (DEG)
-40.00 360.0
AZIM(DEG)
-40.00 360.0

C2 (IN)
26.00 6.000
C1 (IN)
26.00 6.000

FILE
7

5 cm

FILE
7

DEVI(DEG)
-1.000 9.000
RB (DEG)
-40.00 360.0
AZIM(DEG)
-40.00 360.0

C2 (IN)
26.00 6.000
C1 (IN)
26.00 6.000

SENSOR MEASURE POINT TO TENSION REFERENCE POINT

RB	.0	METER	AZIM	.0	METER
FEP1	.0	METER	DEVI	.0	METER
REFE	.0	METER	FEP2	.0	METER
EMEX	.0	METER	RC	.0	METER
C2	.0	METER	C1	.0	METER
RC2	.0	METER	RC1	.0	METER
TEMP	.0	METER	PP	.0	METER
FC0	.0	METER	TENS	.0	METER
FC2	.0	METER	FC1	.0	METER
FC4	.0	METER	FC3	.0	METER
SHDT	.0	METER			

PARAMETERS

NAME	VALUE	UNIT	NAME	VALUE	UNIT
MCT	36	DEG	BS	12.25	IN
BHS	OPEN		STYP	HDSD	
DO	0.0				

DEVI(DEG)
-1.000 9.000
RB (DEG)
-40.00 360.0
AZIM(DEG)
-40.00 360.0

C2 (IN)
26.00 6.000
C1 (IN)
26.00 6.000

FILE
6 REPEAT SECTION



FILE
6

DEVI(DEG)
-1.000 9.000
RB (DEG)
-40.00 360.0
AZIM(DEG)
-40.00 360.0

C2 (IN)
26.00 6.000
C1 (IN)
26.00 6.000

SENSOR MEASURE POINT TO TENSION REFERENCE POINT