

Cutting	Sample	Descriptions	Peterson #1	APW.	12/4/70.
Interval.	%	DESCRIPTION.			
8940-50.	70.	SILTSTONE.	brn firm carb. mic.		
	20	COAL	blk brittle, vitreous		
	10	SANDSTONE	AA-		
8952-60.	50	SANDSTONE.	wh. f-vfg hd. tight wh. dolic conc. mic fl.		
	40	SILTSTONE	AA.		
	10	COAL			
8960-70.	50	SILTSTONE	AA		
	30	SANDSTONE	wh. dom ffg. minor mg ang. hd. tight.		
	20.	COAL	AA.		
8970-80	60	SANDSTONE.	AA		
	30	SILTSTONE.	AA		
	10	COAL	AA		
8980-90.	60	COAL	AA		
	20	SILTSTONE	AA		
	20.	SANDSTONE	AA:		
9000-9020	80.	SANDSTONE.	wh f-mg. ws. sa-r. clear. hd tight dolic cement w/ytlimin fluor. NO cut.		
	20.	SILTSTONE.	aa. Tr coal.		
9000-9010			AS ABOVE.		
9010-9020			AS ABOVE		
9020-9030	70	SILTSTONE.	dk brn firm v carb sli mic.		
	20.	SANDSTONE	AA.		
	10	COAL.	AA		
9030-9040	80	SILTSTONE.	AA		
	10	SANDSTONE	AA		
	10	COAL.	AA		

BHP OIL & GAS DIVISION  
DO NOT RETAIN IN PERSONAL FILES  
**FILE COPY**  
PLEASE RETURN TO  
EXTENSION FILES