

389044

PAGE 2 OF 3  
ATT 60 REC 48

DATE May 30, 1972

ESSO AUSTRALIA LTD.  
SIDEWALL CORE DESCRIPTIONSWELL Pelican-3  
GEOLOGIST Mebberson  
SERVICE COSchlumberger

IES RUN NO 2

SWC RUN NO 1

NO.	DEPTH	REC	ROCK TYPE	MODIFIERS	CAL	COLOR	INDUR DEG	GRAIN SIZE	SRTG	RND	DISS CLAY	STAIN	FLOURESCENCE			CUT FLUOR.		CUT RESIDUE		SHOW	PROB PROD	REMARKS - GAS
													% RK	DISTR 14	INTEN 15	COLOR 16	INTEN 17	COLOR 18	QUAN 19			
29	7000	MF																				
30	6892	1"	sand			wh.gy	frbl.	m.fg.	poor	sa	abt.									NS		slightly laminat
31	6800	1/2"	slt.st	v. carb.		v.dkgy	mfm															laminated
32	6628	1"	sand			gy.wh	fm-fri	vfg	mod	sast	mod									NS		
33	6540	1"	slt.st	sandy carb.		gray	mfm	slt-fg														laminated
34	6400	1"	sand	v. carb.		white	frbl.	vf-f	mod	sa										NS		slightly laminat
35	6257	3/4"	slt.st	sl.carb. sand.		gray	fm-fri															laminated
36	6200	1"	sand	v. carb.		bk-wh	frble	vf-f	mod	sa										NS		very laminated
37	5980	1 3/8"	slt.st	banded ol.gy slt.sandy		lt.gy	fm.															laminated
38	5950	1 3/8"	slt.st	sl.carb banded		lt.gy	fm.															laminated
39	5920	1 1/2"	sand	v. carb.		gray	fm-fri	fg-slt	mod	sa										NS		non-laminated almost silt ston
40	5890	1 1/2"	slt.st	sandy, carb		dk.gy	fm-fri															mottled
41	5860	1 1/2"	slt.st	sandy, carb		dk.gy	fm-fri															mottled
42	5803	1 1/2"	shale	pyritic v. carb.		dk. brown	fm.	f.														
43	5700	1 3/4"	shale	pyritic v. carb.		dk. brown	fm.	f.														
44	5600	1 3/4"	shale	v. carb.		br.blk	fm.															
45	5550	1 3/4"	shale	v. carb.		blk dk.br	hd.															
46	5520	1 1/2"	shale	pyritic v. carb.		dk.br -blk	fm.															
47	5490	1 1/2"	shale	pyritic v. carb.		dk.br	fm.															
48	5460	1 3/4"	slt.st	sl. sandy		br.gy	fm-fri	vf-slt														sl.banded
49	5430	1 3/4"	slt.st	sl. sandy		gr-br.	fm-fri	vf-slt														mottled sl.banded
50	5400	1 3/8"	slt.st	sandy		brown	fm-fri	silt														banded
51	5200	1 3/4"	slt.st	v. sandy		brown	fm.fri	fg-slt														
52	5000	1 3/4"	marl.	silty	vry	gy-gn	soft															mottled
53	4800	1 1/2"	shale	calc-pyr	v.	gn-br	fm															
54	4600	1 1/2"	marl.	silty	v.	gy-gn	soft	fm														mottled
55	4400	SO																				
56	4200	1 3/4"	marl.		v.	gy-gn	m.sft															

FILED DATA  
 0867