ENCLOSURE 10a 389109 OR-353

OFFSHORE 10

SCHLUMBERGER

MICROLATEROLOG-MICROLOG
(WITH CALIPER)

COMPANY ESSO

WELL PELICAN 3

FIELD or LOCATION PELICAN

COUNTY AUSTRALIA

FIELD PRINT

COMPANY ESSO AUSTRALIA LTD.

WELL PELICAN 3

FIELD PELICAN

COUNTY AUSTRALIA STATE TASMANIA

LOCATION LAT: 40° 15' 43" S LONG: 145° 51' 51" E.

Other Services: L7, ST.

Sec. Twp. Rge.

Permanent Datum: MSL Elev. 0

Log Measured From KB, 32 Ft. Above Perm. Datum

Drilling Measured From KB

Elev.: K.B. 32 D.F. 31 G.L. -263

Date	MAY 29 1972		
Run No.	1, 5", 2"		
Depth—Driller	9534		
Depth—Logger	9540		
Btm. Log Interval	9537		
Top Log Interval	8000		
Casing—Driller	13 3/8 @ 3029	@	@
Casing—Logger	3041		
Bit Size	12 1/4		
Type Fluid in Hole	LIGNOSULPHONATE + POT. CHLORIDE		
Dens. | Visc.	11.6 | 46		
pH | Fluid Loss	10.5 | 6.4 ml	ml	ml
Source of Sample	FLOWLINE		
Rm @ Meas. Temp.	0.395 @ 92°F	@ °F	@ °F
Rmf @ Meas. Temp.	0.354 @ 80°F	@ °F	@ °F
Rmc @ Meas. Temp.	0.641 @ 80°F	@ °F	@ °F
Source: Rmf Rmc	PRESS		
Rm @ BHT	0.18 @ 209°F	@ °F	@ °F
Time Since Circ.	10 HRS.		
Max. Rec. Temp.	207/209°F	°F	°F
Equip. | Location	2080 | SAL		
Recorded By	CHAFFE		
Witnessed By	WEBBERSON.		

FOLD HERE The well name, location and borehole reference data were furnished by the customer.

REMARKS CALIPER MALFUNCTION

Changes in Mud Type or Additional Samples		
Date | Sample No.		
Depth—Driller		
Type Fluid in Hole		
Dens. | Visc.		
ph | Fluid Loss	ml	ml
Source of Sample		
Rm @ Meas. Temp.	@ °F	@ °F
Rmf @ Meas. Temp.	@ °F	@ °F
Rmc @ Meas. Temp.	@ °F	@ °F
Source: Rmf Rmc		
Rm @ BHT	@ °F	@ °F
Rmf @ BHT	@ °F	@ °F
Rmc @ BHT	@ °F	@ °F

Scale Changes			
Type Log	Depth	Scale Up Hole	Scale Down Hole

Equipment Data				
Run No.	Tool Type	Pad Type	Tool Pos.	Other
1	MPT-C	MLL/ML		

Equip. Used: CART. No.: MPC-FB 218
PANEL No.: MPP-CB 211
SONDE No.: MPS-D 742

RESISTIVITY ohms — m²/m	DEPTHS	RESISTIVITY ohms — m²/m
Micro Inverse 1" x 1" 5 — 0		MICROLATEROLOG 0.2 1.0 10 100 1000 2000
Micro Normal 2" 5 — 0		
MICROCALIPER Hole Diameter in Inches 8" BIT SIZE 18"	2"	

MICROCALIPER Hole Diameter in Inches 8" BIT SIZE 18"	5"	
Micro Inverse 1" x 1" 5 — 0		
Micro Normal 2" 5 — 0		MICROLATEROLOG 0.2 1.0 10 100 1000 2000
RESISTIVITY ohms — m²/m	DEPTHS	RESISTIVITY ohms — m²/m

COMPANY ESSO AUSTRALIA LTD.
WELL PELICAN 3
FIELD PELICAN
COUNTY AUSTRALIA STATE TASMANIA

SCHL. FR 9537
SCHL. TD 9540
DRLR TD 9534
Elev: KB 32 DF 31 GL -263

MUD LOG RECORDED RUNNING DOWNHOLE WITH SONDE COLLAPSED.