



THE BROKEN HILL PROPRIETARY CO. LTD.

OIL AND GAS DIVISION
(HEMATITE PETROLEUM PTY. LTD.)

CORE DESCRIPTION

Core No. 2 (pg 2)

WELL: Pelican # 4.

Interval Cored 9563 - 9606 ft., * Cut 43 ft., Recovered 43 ft., (100 %) Fm. E.V.C.M.
Bit Type C-20, Bit Size 8 15/32 in., Desc. by B.N. Atkins Date 10/2/79.

Depth & Coring Rate (min./ft.)	Graphic (1" = 5')	Shows	Interval (ft.)	Descriptive Lithology
9600			(cont.)	
			9600' 4" - 9603' 2";	Siltst / v.f. Sst - mid-dk gy, thin interbeds up to 2 cm sub // 10-15° v. firm. Common burrows, rare scouring, flame structures, convolute bedding. Massive at 9602' 3" - 9" dk gy, extensive bioturbation.
9605			9603' 2" - 9606'	Sh, dk gy, sub-fissile, common thin (< 4 cm) siltst / v.f. sst beds. Dip > 10°.

REMARKS:

* NOTE: THESE DEPTHS HAVE SUBSEQUENTLY BEEN ADJUSTED DOWN 10 ft (i.e. 9573' - 9616') TO MATCH LOGS.

