391171

d7

OR-354

ENCLOSURE 76

Schlumberger

CALIPER LOG

COUNTY AUSTRALIA
FIELD or LOCATION WILDCAT
WELL PELICAN #4
COMPANY HEMATITE PET.LTD.

COMPANY Hematite Petroleum Co.
WELL Pelican #4
FIELD Wildcat
COUNTY Australia STATE Tasmania
LOCATION 40° 21' 38.30" S 145° 52' 17.70" E
Sec. Twp. Rge.
Other Services: ISF-BHC

Permanent Datum: MSL, Elev. 0
Log Measured From KB, 82 Ft. Above Perm. Datum
Drilling Measured From KB

Elev.: K.B. 82
D.F. 81
G.L. -254

Date	20-1-79			
Run No.	ONE			
Depth—Driller	2864			
Depth—Logger	2862			
Btm. Log Interval	2848			
Top Log Interval	762			
Casing—Driller	20" @ 761	@	@	@
Casing—Logger	762			
Bit Size	17½"			
Type Fluid in Hole	Drispac Sea Water			
Dens. | Visc.	9.1 | 43			
pH | Fluid Loss	10.0 | 20.4 ml	ml	ml	ml
Source of Sample	FLOWLINE			
R_m @ Meas. Temp.	0.23 @ 77 °F	@ °F	@ °F	@ °F
R_{mf} @ Meas. Temp.	0.19 @ 77 °F	@ °F	@ °F	@ °F
R_{mc} @ Meas. Temp.	0.38 @ 77 °F	@ °F	@ °F	@ °F
Source: R_{mf} | R_{mc}	PRESS | PRESS			
R_m @ BHT	0.16 @ 110 °F	@ °F	@ °F	@ °F
Time Since Circ.	6 Hrs.			
Max. Rec. Temp.	110 °F	°F	°F	°F
Equip. | Location	3501 | SEA			
Recorded By	S.BRISCOE			
Witnessed By	D.WARNER			

FOLD HERE The well name, location and borehole reference data were furnished by the customer.

REMARKS

Changes in Mud Type or Additional Samples

Date | Sample No.		
Depth—Driller		
Type Fluid in Hole		
Dens. | Visc.		
ph | Fluid Loss	ml	
Source of Sample		
R_m @ Meas. Temp.	@ °F	@ °F
R_{mf} @ Meas. Temp.	@ °F	@ °F
R_{mc} @ Meas. Temp.	@ °F	@ °F
Source: R_{mf} | R_{mc}		
R_m @ BHT	@ °F	@ °F
R_{mf} @ BHT	@ °F	@ °F
R_{mc} @ BHT	@ °F	@ °F

Scale Changes

Type Log	Depth	Scale Up Hole	Scale Down Hole

Equipment Data

Run No.	Tool Type	Pad Type	Tool Pos.	Other
1	PGT-E	PDH-DB	Excent	

5 cm

SWS-1664-A

15 25

CALIPER
HOLE DIAMETER IN INCHES

5"

5 cm

DEPTHS

COMPANY Hematite Petroleum Co.Pty.Ltd.
WELL Pelican #4
FIELD Wildcat
COUNTY Australia STATE Tasmania