

## b. Drill Collars:

- (1) Six (6) 9½" O.D. x 30" long spiral drill collars
- (2) Thirty (30) 7-¾" O.D. x 2-13/16" I.D. x 30' long spiral collars.
- (3) Thirty (30) 6-1/2" O.D. x 2-13/16" I.D. x 30' long spiral collars.

(Note: Drill collars recessed for elevator and slip handling, have API connection and stress relieved grooves on pins and bore back in boxes. Threads and stress relief grooves cold worked and treated for anti-galling.

## c. Bumper Subs

- (1) Two (2) 6½" O.D. with 5 ft. stroke.
- (2) Two (2) 8" O.D. with 5 ft. stroke.

## d. Kelly- Two (2) 5-1/4" Hex type

## e. Subs and Bit Subs- As required for contractors drill string

## f. Sufficient box and pin thread protectors for all Contractor's equipment

## g. Bit Breakers for 26", 17½", 12½" and 8½".

## h. Pipe Wipers for 5" drill pipe

4. Blowout Preventers, Subsea Equipment and Control Equipment

## a. Diverter System - Regan Model KFDH-3.

## b. One (1) 30" Cameron Pin Connector

c. 18-3/4"-10,000 psi WP BOP stack consisting of the following major components (H<sub>2</sub>S trim):

- (1) Flex Joint - Cameron 18-3/4" with RCK connector
- (2) Riser Connector - C.I.W. 18-3/4"-10,000 psi WP Collet connector
- (3) Annular Preventers - Two (2) Cameron 18-3/4", 5000 psi.
- (4) Ram preventer - Two (2) double type "U" II Cameron 18-3/4" - 10,000 psi WP BOP's
- (5) Wellhead connector - Cameron, 18-3/4"-10,000 psi W.P. Collet connector.