446249

TEST STRING

TEST NUMBER	RIG NAME	DATE (DAY MO. YR.)	PAGE	OF
DST #1	DIAMOND M. EPOCH	14MAR86	1	1

CUSTOMER	WELL NAME OR NUMBER	FIELD	AREA
AMOCO AUSTRALIA PETROLEUM.CO.	PELICAN #5	PELICAN	BASS STRAIT

KB ELEVATION (FT)	GROUND ELEV./WATER DEPTH (FEET)	REFERENCE ELEV.	MUD WT. (LBS./FT.)	INTERVAL TESTED (FEET)
321	72.6	0 TIDE	15.8	3672-3699M

TOP OF HOLE	DEPTH (FEET)		DEPTH (FEET)	ITEM #	DESCRIPTION	OUTSIDE DIAMETER (INCHES)	INSIDE DIAMETER (INCHES)	LENGTH (FEET)
				1	SURFACE TEST TREE		2.880	
				2	3 JOINTS HW DRILL PIPE	6.500	3.125	91.28
				3	PUP JOINT HW DRILL PIPE	6.500	3.125	5.02
				4	XO 4-1/2IF X 4-1/2 4 STUB ACME			
				5	SUBSEA LUBRICATOR VALVE	10.750	2.880	9.50
				6	7 JOINTS HW DRILL PIPE	6.500	3.125	212.74
				7	XO 4-1/2IF X 4-1/2 4 STUB ACME			
				8	SUBSEA TEST TREE	10.750	2.940	
				9	XO 4-1/2 4STUB ACME X 3-1/2VAM	6.250		1.00
				10	333 JOINTS VAM TUBING	3.500	2.750	
				11	XO 3-1/2VAM BOX X 3-1/2PH6 PIN	4.750	2.750	1.00
				12	SRO NIPPLE	4.625	2.230	2.00
				13	XO 3-1/2PH6 BOX X 3-1/2IF PIN	4.750	2.750	1.00
				14	FULL FLOW SAFETY VALVE	5.000	2.250	4.76
				15	1 STAND DRILL COLLARS	4.750	2.312	93.52
				16	SLIP JOINT	5.000	2.250	18.16
				17	SLIP JOINT	5.000	2.250	15.66
				18	SLIP JOINT	5.000	2.250	13.16
				19	3 STANDS DRILL COLLARS	4.750	2.312	277.91
				20	FULL FLOW HYD CIRC VALVE	4.625	2.250	7.22
				21	SLIP JOINT	5.000	2.250	18.16
				22	4 STANDS DRILL COLLARS	4.750	2.312	370.52
				23	LPR-M2 CIRC SAFETY VALVE	5.000	2.250	19.40
				24	FULL FLOW DRAIN VALVE	5.000	2.250	1.00
				25	LPR-N TEST VALVE	5.000	2.250	16.40
				26	FULL FLOW HYD CIRC VALVE	4.625	2.250	7.22
				27	JARS	4.625	2.250	5.00
				28	BUNDLE CARRIER	5.030	2.187	7.97
				29	XO 3-1/2IF BOX X 2-7/8EUE PIN	4.750	2.310	1.18
				30	RTTS SAFETY JOINT	4.870	2.440	3.30
			11595	31	RTTS PACKER	5.750	2.400	4.52
				32	XO 2-7/8EUE PIN X 3-1/2FH PIN	4.620	2.250	1.04
				33	XO 3-1/2FH BOX X 3-1/2IF PIN	4.750	2.310	1.03
				34	DRILL PIPE	3.500	2.764	31.00
				35	XO 3-1/2IF BOX X 3-1/2EUE PIN	4.750	2.250	1.00
				36	WIRELINE RE-ENTRY GUIDE			0.83
				37				
		BOTTOM OF HOLE		38				