



TEST STRING

446250

| | | | | |
|-------------|------------------|--------------------|------|----|
| TEST NUMBER | RIG NAME | DATE (DAY MO. YR.) | PAGE | OF |
| DST #2A & 3 | DIAMOND M. EPOCH | 20MAR86 | 1 | 1 |

| | | | |
|-------------------------------|---------------------|---------|-------------|
| CUSTOMER | WELL NAME OR NUMBER | FIELD | AREA |
| AMOCO AUSTRALIA PETROLEUM CO. | PELICAN #5 | PELICAN | BASS STRAIT |

| TOP OF HOLE | DEPTH (FEET) | DEPTH (FEET) | KB ELEVATION (FT) | GROUND ELEV./WATER DEPTH (FEET) | REFERENCE ELEV. | MUD WT. (LBS./FT.) | INTERVAL TESTED (FEET) SEE DESC. | | |
|-------------|----------------|--------------|-------------------|---------------------------------|-----------------|--------------------|-------------------------------------|--------------------------|---------------|
| | | | 321 | 73 | RKB | 15.0 | | | |
| | | | ITEM # | DESCRIPTION | | | OUTSIDE DIAMETER (INCHES) | INSIDE DIAMETER (INCHES) | LENGTH (FEET) |
| | | | 1 | OTIS CONTROL HEAD | | | | | |
| | | | 2 | 3 JOINTS 5-INCH DRILL PIPE | | | 5.000 | 4.276 | 91.28 |
| | | | 3 | PUP JOINT | | | 5.000 | 4.276 | 5.02 |
| | | | 4 | OTIS SUBSEA LUBRICATOR VALVE | | | 10.750 | 2.940 | 9.50 |
| | | | 5 | 7 JOINTS 5-INCH DRILL PIPE | | | 5.000 | 4.276 | 212.74 |
| | | | 6 | OTIS SUBSEA TEST TREE | | | 10.750 | 2.940 | 20.00 |
| | | | 7 | 108 STANDS TUBING | | | 3.500 | 2.750 | |
| | | | 8 | XD 3-1/2VAM BOX X 3-1/2PH6 PIN | | | 4.750 | 2.750 | 1.00 |
| | | | 9 | SRO LATCH NIPPLE | | | 4.625 | 2.750 | 2.00 |
| | | | 10 | XD 3-1/2PH6 BOX X 3-1/2IF PIN | | | 4.750 | 2.750 | 1.00 |
| | | | 11 | FULL FLOW SAFETY VALVE | | | 5.000 | 2.250 | 4.00 |
| | | | 12 | 1 STAND DRILL COLLAR | | | 4.750 | 2.312 | 93.52 |
| | | | 13 | SLIP JOINT | | | 5.000 | 2.250 | 18.16 |
| | | | 14 | SLIP JOINT | | | 5.000 | 2.250 | 13.66 |
| | | | 15 | SLIP JOINT | | | 5.000 | 2.250 | 13.16 |
| | | | 16 | 3 STANDS DRILL COLLAR | | | 4.750 | 2.312 | 277.91 |
| | | | 17 | FULL FLOW HYD CIRC VALVE | | | 4.625 | 2.250 | 7.22 |
| | | | 18 | SLIP JOINT | | | 5.000 | 2.250 | 13.16 |
| | | | 19 | 4 STANDS DRILL COLLAR | | | 4.750 | 2.312 | 370.52 |
| | | | 20 | LPR-M2 CIRC SAFETY VALVE | | | 5.000 | 2.250 | 18.40 |
| | | | 21 | FULL FLOW DRAIN VALVE | | | 5.000 | 2.250 | 1.00 |
| | | | 22 | LPR-N TESTER VALVE | | | 5.000 | 2.250 | 16.40 |
| | | | 23 | FULL FLOW HYD CIRC VALVE | | | 4.625 | 2.250 | 7.22 |
| | | | 24 | JARS | | | 4.625 | 2.250 | 5.00 |
| | | | 25 | BUNDLE CARRIER | | | 5.030 | 2.187 | 7.97 |
| | | | 26 | XD 3-1/2IF BOX X 2-7/8EUE PIN | | | 4.750 | 2.310 | 1.18 |
| | | | 27 | RTTS SAFETY JOINT | | | 4.870 | 2.440 | 3.30 |
| | | 11024 | 28 | RTTS PACKER | | | 5.750 | 2.460 | 4.52 |
| | | | 29 | XD 2-7/8EUE PIN X 3-1/2FH PIN | | | 4.820 | 2.250 | 1.04 |
| | | | 30 | XD 3-1/2FH BOX X 3-1/2IF PIN | | | 4.750 | 2.310 | 1.03 |
| | | | 31 | 1 JOINT DRILL PIPE | | | 3.500 | 2.764 | 31.00 |
| | | | 32 | XD 3-1/2IF BOX X 3-1/2EUE PIN | | | 4.750 | 2.250 | 1.00 |
| | | | 33 | WIRELINE RE-ENTRY GUIDE | | | | | 0.83 |
| | | | 34 | | | | | | |
| | | | 35 | PACKER SET AT 11024 FEET | | | | | |
| | | | 36 | | | | | | |
| | | | 37 | | | | | | |
| | | | 38 | | | | | | |
| | BOTTOM OF HOLE | | | | | | | | |