



FIELD READINGS
SINGLE STAGE UNIT
OEC - 905-1-A

446286

| | | | | | |
|--------------------------|--|--|---------------------------------------|------------------|-----------------|
| TEST NO. DST#1 | WELL NAME OR NUMBER PELICAN #5 | TEST UNIT DESCRIPTION 1440PSI 3PHASE SEPARATOR | DATE (DAY, MO. YR.) 14MAR86 | PAGE 2 | OF 10 |
|--------------------------|--|--|---------------------------------------|------------------|-----------------|

| | | | | |
|--|-------------------------|-------------------------------|----------------------------|----------------------------------|
| CUSTOMER AMOCO AUSTRALIA PETROLEUM CO. | FIELD PELICAN | FORMATION SANDSTONE | OIL METER SIZE 0 | METER RANGE (BBLs) --- |
|--|-------------------------|-------------------------------|----------------------------|----------------------------------|

| | | | | | |
|---|--|--|--------------------------------|---|---|
| INTERVAL TESTED 3672-3699 MTR | BHP SURVEY DEPTH (FT.) (FT.) | GAS PRODUCED TO <input type="checkbox"/> PIPELINE <input checked="" type="checkbox"/> FLARE | GAS METER RUN SIZE 0 | DIFF. RANGE (INS. H ₂ O) (INS) 0-100 | STATIC PRESSURE TAKEN <input type="checkbox"/> UPSTREAM <input checked="" type="checkbox"/> DOWNSTREAM |
|---|--|--|--------------------------------|---|---|

| TIME | | WELLHEAD DATA | | | DOWNHOLE DATA | | FLOW CONTROL | | GAS METERING | | | | | OIL OR CONDENSATE METERING | | | | WATER METERING | | | |
|---------------|--------------------------|---|-------|---------------|---------------|------|--------------|--------------|--------------|---------------|-----------------------|-------|---------------------|--|-------------------|-------------|----------------|---|----------|--|----|
| DAY | FLOW OR SHUT-IN DURATION | TUBING PRESS. | TEMP. | CASING PRESS. | BHP | BHT | MAN. CHOKE | HEATER CHOKE | ORIFICE SIZE | STATIC PRESS. | DIFF. PRESS. | TEMP. | GAS GRAVITY (AIR=1) | # 1 TANK OR METER READING | # 1 OIL TEMP | OIL GRAVITY | W _i | # 1 TANK OR METER READING | SALINITY | | |
| 24 HOUR CLOCK | (HOURS) | (PSIG) | (°F) | (PSIG) | (PSIG) | (°F) | (64TH) IN) | (64TH) IN) | (INS) | (PSIG) | (IN H ₂ O) | (°F) | % H ₂ S | # 2 TANK OR METER READING (INS OR BBL) | # 2 OIL TEMP (°F) | @ 60°F API | BSW (%) | # 2 TANK OR METER READING (INS. OR BBL) | (%) | | |
| 1 | 14 | RIGGED UP PERFORATING GUNS | | | | | | | | | | | | | | | | | | | 1 |
| 1755 | 2.98 | 0 | 66 | 1840 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 2 | 14 | PUMPED CLOSE SUBSEA LUBRICATOR VALVE | | | | | | | | | | | | | | | | | | | 2 |
| 1813 | 3.28 | 1 | 65 | 1840 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 3 | 14 | GUNS RAN IN HOLE | | | | | | | | | | | | | | | | | | | 3 |
| 1813 | 3.28 | 1 | 65 | 1840 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 4 | 14 | | | | | | | | | | | | | | | | | | | | |
| 1840 | 3.73 | 2 | 65 | 1840 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 5 | 14 | | | | | | | | | | | | | | | | | | | | |
| 1845 | 3.81 | 3 | 65 | 1840 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 6 | 14 | | | | | | | | | | | | | | | | | | | | |
| 1900 | 4.06 | 7 | 65 | 1820 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 7 | 14 | | | | | | | | | | | | | | | | | | | | |
| 1915 | 4.31 | 18 | 65 | 1820 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 8 | 14 | | | | | | | | | | | | | | | | | | | | |
| 1930 | 4.56 | 35 | 65 | 1820 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 9 | 14 | | | | | | | | | | | | | | | | | | | | |
| 1945 | 4.81 | 68 | 64 | 1820 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 10 | 14 | | | | | | | | | | | | | | | | | | | | |
| 2000 | 5.06 | 70 | 64 | 1820 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 11 | 14 | PERFORATING GUNS UNABLE TO PASS 3258 METRES | | | | | | | | | | | | | | | | | | | 11 |
| 2005 | 5.14 | 65 | 64 | 1820 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 12 | 14 | STARTED PULLING OUT OF HOLE | | | | | | | | | | | | | | | | | | | 12 |
| 2005 | 5.14 | 65 | 64 | 1820 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 13 | 14 | | | | | | | | | | | | | | | | | | | | |
| 2015 | 5.31 | 55 | 64 | 1800 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 14 | 14 | | | | | | | | | | | | | | | | | | | | |
| 2030 | 5.56 | 32 | 63 | 1800 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 15 | 14 | | | | | | | | | | | | | | | | | | | | |
| 2100 | 6.06 | 15 | 63 | 1800 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 16 | 14 | PERFORATING GUNS AT SURFACE | | | | | | | | | | | | | | | | | | | 16 |
| 2122 | 6.43 | 13 | 63 | 1800 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |
| 17 | 14 | PUMPED CLOSE SUBSEA LUBRICATOR VALVE | | | | | | | | | | | | | | | | | | | 17 |
| 2125 | 6.48 | 13 | 63 | 1800 | 0.0 | 0 | 0 | | | | | | | | | | | | | | |