



FIELD READINGS
SINGLE STAGE UNIT
OEC - 905-1-A

446287

TEST NO. DST#1	WELL NAME OR NUMBER PELICAN #5	TEST UNIT DESCRIPTION 1440PSI 3PHASE SEPARATOR	DATE (DAY, MO. YR.) 14MAR86	PAGE 3	OF 10
--------------------------	--	--	---------------------------------------	------------------	-----------------

CUSTOMER AMOCO AUSTRALIA PETROLEUM.CO.	FIELD PELICAN	FORMATION SANDSTONE	OIL METER SIZE 0	METER RANGE (BBLs) ---
--	-------------------------	-------------------------------	----------------------------	----------------------------------

INTERVAL TESTED 3672-3699 MTR	BHP SURVEY DEPTH (FT.) (FT.)	GAS PRODUCED TO <input type="checkbox"/> PIPELINE <input checked="" type="checkbox"/> FLARE	GAS METER RUN SIZE 0	DIFF. RANGE (INS. H ₂ O) 0-100	STATIC PRESSURE TAKEN <input type="checkbox"/> UPSTREAM <input checked="" type="checkbox"/> DOWNSTREAM
---	--	--	--------------------------------	---	---

TIME		WELLHEAD DATA			DOWNHOLE DATA		FLOW CONTROL		GAS METERING				OIL OR CONDENSATE METERING				WATER METERING			
DAY	FLOW OR SHUT-IN DURATION	TUBING PRESS.	TEMP.	CASING PRESS.	B H P	B H T	MAN. CHOKE	HEATER CHOKE	ORIFICE SIZE	STATIC PRESS.	DIFF. PRESS.	TEMP.	GAS GRAVITY (AIR=1)	# 1 TANK OR METER READING	# 1 OIL TEMP	OIL GRAVITY	W _i	# 1 TANK OR METER READING	SALINITY	
24 HOUR CLOCK	(HOURS)	(PSIG)	(°F)	(PSIG)	(PSIG)	(°F)	(64TH) IN)	(64TH) IN)	(INS)	(PSIG)	(IN H ₂ O)	(°F)	% H ₂ S	# 2 TANK OR METER READING (INS OR BBL)	# 2 OIL TEMP (°F)	@ 60°F °API	BSW (%)	# 2 TANK OR METER READING (INS. OR BBL)	(%)	
1	14	BLED DOWN SURFACE PRESSURE																		1
2130	6.56	0	63	1800	0.0	0	0													
2	14	SCHLUMBERGER LUBRICATOR RIGGED DOWN																		2
2225	7.48	0	63	1800	0.0	0	0													
3	14	OTIS LUBRICATOR RIGGED UP AND PRESSURE TESTED																		3
2315	8.31	0	62	1800	0.0	0	0													
4	14	PUMPED OPEN SUBSEA LUBRICATOR VALVE																		4
2350	8.89	0	60	1860	0.0	0	0													
5	14	WIRELINE GAUGE CUTTER RAN IN HOLE																		5
2350	8.89	0	60	1860	0.0	0	0													
6	15	OTIS WIRELINE BACK AT SURFACE																		6
0145	10.81	0	60	1820	0.0	0	0													
7	15	PUMPED CLOSE SUBSEA LUBRICATOR VALVE																		7
0145	10.81	0	60	1820	0.0	0	0													
8	15	RIGGED DOWN LUBRICATOR																		8
0145	10.81	0	60	1820	0.0	0	0													
9	15	SCHLUMBERGER LUBRICATOR RIGGED UP AND																		9
0305	12.14	0	58	1820	0.0	0	0													
10	15	PRESSURE TESTED																		10
0305	12.14	0	58	1820	0.0	0	0													
11	15	PERFORATING GUNS PICKED UP INTO LUBRICATOR																		11
0500	14.06	0	58	1820	0.0	0	0													
12	15	SUBSEA LUBRICATOR VALVE PUMPED OPEN																		12
0525	14.48	0	58	1820	0.0	0	0													
13	15	PERFORATING GUNS RAN IN THE HOLE																		13
0525	14.48	0	58	1820	0.0	0	0													
14	15																			
0605	15.14	45	57	1820	0.0	0	0													
15	15																			
0615	15.31	150	57	1820	0.0	0	0													
16	15																			
0630	15.56	450	57	1820	0.0	0	0													
17	15																			
0645	15.81	680	57	1820	0.0	0	0													

Computer - Form Toppan (Hou)