



FIELD READINGS
SINGLE STAGE UNIT
OEC - 905-1-A

TEST NO. DST#2A	WELL NAME OR NUMBER PELICAN #5	TEST UNIT DESCRIPTION 1440PSI 3PHASE SEPARATOR	DATE (DAY, MO. YR.) 20MAR86	PAGE 2	OF 4
---------------------------	--	--	---------------------------------------	------------------	----------------

CUSTOMER AMOCO AUSTRALIA PETROLEUM.CO.	FIELD PELICAN	FORMATION SANDSTONE	OIL METER SIZE 0	METER RANGE (BBLs) ---
--	-------------------------	-------------------------------	----------------------------	---------------------------

INTERVAL TESTED 3612-3618M	BHP SURVEY DEPTH (FT.)	GAS PRODUCED TO <input type="checkbox"/> PIPELINE <input checked="" type="checkbox"/> FLARE	GAS METER RUN SIZE 5.761 (INS)	DIFF. RANGE (INS. H ₂ O) 0-100	STATIC PRESSURE TAKEN <input type="checkbox"/> UPSTREAM <input checked="" type="checkbox"/> DOWNSTREAM
--------------------------------------	------------------------	--	--	---	---

TIME	WELLHEAD DATA				DOWNHOLE DATA				FLOW CONTROL				GAS METERING				OIL OR CONDENSATE METERING				WATER METERING	
	DAY	FLOW OR SHUT-IN DURATION	TUBING PRESS.	TEMP.	CASING PRESS.	B H P	B H T	MAN. CHOKE	HEATER CHOKE	ORIFICE SIZE	STATIC PRESS.	DIFF. PRESS.	TEMP.	GAS GRAVITY (AIR=1)	# 1 TANK OR METER READING	# 1 OIL TEMP	OIL GRAVITY	W _i	# 1 TANK OR METER READING	SALINITY		
24 HOUR CLOCK	(HOURS)	(PSIG)	(°F)	(PSIG)	(PSIG)	(°F)	(64TH IN)	(64TH IN)	(INS)	(PSIG)	(IN H ₂ O)	(°F)	% H ₂ S	# 2 TANK OR METER READING (INS OR BBL)	# 2 OIL TEMP (°F)	@ 60°F °API	BSW (%)	# 2 TANK OR METER READING (INS. OR BBL)	(%)			
1 20																						
0915	0.26	0	69	1960	0.0	0	16															
2 20																						
0930	0.51	0	69	1940	0.0	0	16															
3 20	STARTED RIGGING UP SCHLUMBERGER LUBRICATOR																					
0945	0.76	0	69	1910	0.0	0	16															
4 20																						
1000	1.01	0	69	1900	0.0	0	16															
5 20																						
1015	1.26	0	69	1900	0.0	0	16															
6 20																						
1030	1.51	0	69	1880	0.0	0	16															
7 20	WELL SHUT-IN. PUMPED S.S.L.V. CLOSE																					
1035	1.59	0	69	1880	0.0	0	0															
8 20	PRESSURE TESTED LUBRICATOR TO 5000 PSI - OKAY																					
1100	0.41	0	69	1900	0.0	0	0															
9 20	PUMPED OPEN SUBSEA LUBRICATOR VALVE																					
1235	1.99	100	65	1840	0.0	0	16															
10 20	WELL OPENED TO FLARE ON 16/64" ADJUSTABLE CHOKE																					
1235	1.99	100	65	1840	0.0	0	16															
11 20	SCHLUMBERGER PRODUCTION LOGGING TOOL RAN IN HOLE																					
1236	0.01	10	65	1840	0.0	0	16															
12 20																						
1237	0.03	1	65	1840	0.0	0	16															
13 20																						
1238	0.04	1	65	1840	0.0	0	16															
14 20																						
1239	0.06	1	65	1840	0.0	0	16															
15 20																						
1240	0.08	0	65	1840	0.0	0	16															
16 20																						
1245	0.16	0	65	1840	0.0	0	16															
17 20																						
1300	0.41	0	65	1820	0.0	0	16															