



FIELD READINGS
SINGLE STAGE UNIT
OEC - 905-1-A

446302

| | | | | | |
|---------------------------|--|--|---------------------------------------|------------------|----------------|
| TEST NO. DST#2A | WELL NAME OR NUMBER PELICAN #5 | TEST UNIT DESCRIPTION 1440PSI 3PHASE SEPARATOR | DATE (DAY, MO. YR.) 20MAR86 | PAGE 3 | OF 4 |
|---------------------------|--|--|---------------------------------------|------------------|----------------|

| | | | | |
|--|-------------------------|-------------------------------|----------------------------|---------------------------|
| CUSTOMER AMOCO AUSTRALIA PETROLEUM.CO. | FIELD PELICAN | FORMATION SANDSTONE | OIL METER SIZE 0 | METER RANGE (BBLs) --- |
|--|-------------------------|-------------------------------|----------------------------|---------------------------|

| | | | | | |
|--------------------------------------|------------------------|--|--|---|---|
| INTERVAL TESTED 3612-3618M | BHP SURVEY DEPTH (FT.) | GAS PRODUCED TO <input type="checkbox"/> PIPELINE <input checked="" type="checkbox"/> FLARE | GAS METER RUN SIZE 5.761 (INS) | DIFF. RANGE (INS. H ₂ O) 0-100 | STATIC PRESSURE TAKEN <input type="checkbox"/> UPSTREAM <input checked="" type="checkbox"/> DOWNSTREAM |
|--------------------------------------|------------------------|--|--|---|---|

| TIME | | WELLHEAD DATA | | | DOWNHOLE DATA | | FLOW CONTROL | | GAS METERING | | | | OIL OR CONDENSATE METERING | | | | WATER METERING | | | |
|---------------|--------------------------|---------------|-------|---------------|---------------|-------|--------------|--------------|--------------|---------------|-----------------------|-------|----------------------------|--|-------------------|-------------|----------------|---|----------|--|
| DAY | FLOW OR SHUT-IN DURATION | TUBING PRESS. | TEMP. | CASING PRESS. | B H P | B H T | MAN. CHOKE | HEATER CHOKE | ORIFICE SIZE | STATIC PRESS. | DIFF. PRESS. | TEMP. | GAS GRAVITY (AIR=1) | # 1 TANK OR METER READING | # 1 OIL TEMP | OIL GRAVITY | W _f | # 1 TANK OR METER READING | SALINITY | |
| 24 HOUR CLOCK | (HOURS) | (PSIG) | (°F) | (PSIG) | (PSIG) | (°F) | (64TH IN) | (64TH IN) | (INS) | (PSIG) | (IN H ₂ O) | (°F) | % H ₂ S | # 2 TANK OR METER READING (INS OR BBL) | # 2 OIL TEMP (°F) | @ 60°F °API | BSW (%) | # 2 TANK OR METER READING (INS. OR BBL) | (%) | |
| 1 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1315 | 0.66 | 0 | 65 | 1820 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 2 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1330 | 0.91 | 0 | 65 | 1970 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 3 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1345 | 1.16 | 0 | 65 | 1960 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 4 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1400 | 1.41 | 0 | 64 | 1940 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 5 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1415 | 1.66 | 0 | 64 | 1940 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 6 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1430 | 1.91 | 0 | 64 | 1940 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 7 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1445 | 2.16 | 0 | 64 | 1940 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 8 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1500 | 2.41 | 0 | 64 | 1940 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 9 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1515 | 2.66 | 0 | 64 | 1940 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 10 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1530 | 2.91 | 0 | 64 | 1940 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 11 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1545 | 3.16 | 0 | 64 | 1940 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 12 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1600 | 3.41 | 0 | 64 | 1920 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 13 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1615 | 3.66 | 0 | 64 | 1910 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 14 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1630 | 3.91 | 0 | 64 | 1900 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 15 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1645 | 4.16 | 0 | 64 | 1890 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 16 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1700 | 4.41 | 0 | 64 | 1890 | 0.0 | 0 | 16 | | | | | | | | | | | | |
| 17 | 20 | | | | | | | | | | | | | | | | | | | |
| | 1705 | 4.49 | 0 | 64 | 1890 | 0.0 | 0 | 0 | | | | | | | | | | | | |

PRODUCTION LOGGING TOOL STARTED OUT OF HOLE

PRODUCTION LOGGING TOOL AT SURFACE

SUBSEA LUBRICATOR VALVE PUMPED CLOSE

Computer-Forens Toppan (Houma)