



FIELD READINGS
SINGLE STAGE UNIT
OEC - 905-1-A

446310

TEST NO. DST#4	WELL NAME OR NUMBER PELICAN #5	TEST UNIT DESCRIPTION 1440PSI 3PHASE SEPARATOR	DATE (DAY, MO. YR.) 25MAR86	PAGE 1	OF 12
--------------------------	--	--	---------------------------------------	------------------	-----------------

CUSTOMER AMOCO AUSTRALIA PETROLEUM.CO.	FIELD PELICAN	FORMATION SANDSTONE	OIL METER SIZE 0	METER RANGE (BBLs) ---
--	-------------------------	-------------------------------	----------------------------	----------------------------------

INTERVAL TESTED 3142-3163.5M	BHP SURVEY DEPTH (FT.)	GAS PRODUCED TO <input type="checkbox"/> PIPELINE <input checked="" type="checkbox"/> FLARE	GAS METER RUN SIZE 5.761 (INS)	DIFF. RANGE (INS. H ₂ O) 0-100	STATIC PRESSURE TAKEN <input type="checkbox"/> UPSTREAM <input checked="" type="checkbox"/> DOWNSTREAM
--	------------------------	--	--	---	---

TIME		WELLHEAD DATA			DOWNHOLE DATA		FLOW CONTROL		GAS METERING					OIL OR CONDENSATE METERING				WATER METERING		
DAY	FLOW OR SHUT-IN DURATION	TUBING PRESS.	TEMP.	CASING PRESS.	BHP	BHT	MAN. CHOKE	HEATER CHOKE	ORIFICE SIZE	STATIC PRESS.	DIFF. PRESS.	TEMP.	GAS GRAVITY (AIR=1)	# 1 TANK OR METER READING	# 1 OIL TEMP	OIL GRAVITY	W _f	# 1 TANK OR METER READING	SALINITY	
24 HOUR CLOCK	(HOURS)	(PSIG)	(°F)	(PSIG)	(PSIG)	(°F)	(64TH IN)	(64TH IN)	(INS)	(PSIG)	(IN H ₂ O)	(°F)	% H ₂ S	# 2 TANK OR METER READING (INS OR BBL)	# 2 OIL TEMP (°F)	@ 60°F °API	BSW (%)	# 2 TANK OR METER READING (INS. OR BBL)	(%)	
1	25	THE TEST STRING AND TUBING CONVEYED PERFORATING																		1
0630	0.00																			
2	25	GUNS WERE RAN IN THE HOLE																		2
0630	0.00																			
3	25	THE TEST STRING WAS DISPLACED WITH																		3
0630	0.00	2200	0	0	0.0	0	0	0												
4	25	71 BBLs OF DIESEL																		4
0630	0.00	2200	0	0	0.0	0	0	0												
5	25	BLED DOWN WELLHEAD PRESSURE TO THE OIL BURNERS																		5
0645	0.25																			
6	25	OTIS DOWNHOLE SHUT-IN TOOL RAN IN THE HOLE																		6
1045	4.25																			
7	25	DOWNHOLE SHUT-IN TOOL HUNG UP																		7
1220	5.83																			
8	25	POSSIBLE LANDING NIPPLE																		8
1220	5.83																			
9	25	STARTED PULLING DOWNHOLE SHUT-IN TOOL TO SURFACE																		9
1440	8.16																			
10	25	DOWNHOLE SHUT-IN TOOL IN LUBRICATOR																		10
1600	9.49	0	65	0	0.0	0	0	0												
11	25	PRESSURED UP ON ANNULUS TO OPEN LPR-N TEST TOOL																		11
1607	9.61	100	65	1420	0.0	0	0	0												
12	25	OPENED BUBBLE HOSE TO BLED OFF PRESSURE																		12
1608	9.63	200	65	1420	0.0	0	0	0												
13	25	OPENED CHOKE MFLD. BYPASS TO BLED DOWN PRESSURE																		13
1609	9.64	0	65	1420	0.0	0	0	0												
14	25																			14
1610	9.66	0	65	1420	0.0	0	0	0												
15	25																			15
1615	9.74	0	65	1470	0.0	0	0	0												
16	25	INCREASED ANNULUS PRESSURE. PERFORATED THE ZONE																		16
1620	9.83	0	65	2500	0.0	0	0	0												
17	25																			17
1621	9.84	0	65	2500	0.0	0	0	0												

Computer - Furns Toppan Disc