



FIELD READINGS  
SINGLE STAGE UNIT  
OEC - 905-1-A

446317

TEST NO. <b>DST#4</b>	WELL NAME OR NUMBER <b>PELICAN #5</b>	TEST UNIT DESCRIPTION <b>1440PSI 3PHASE SEPARATOR</b>	DATE (DAY, MO. YR.) <b>26MAR86</b>	PAGE <b>8</b>	OF <b>12</b>
--------------------------	--	--	---------------------------------------	------------------	-----------------

CUSTOMER <b>AMOCO AUSTRALIA PETROLEUM.CO.</b>	FIELD <b>PELICAN</b>	FORMATION <b>SANDSTONE</b>	OIL METER SIZE <b>0</b>	METER RANGE (BBLs) ---
--	-------------------------	-------------------------------	----------------------------	---------------------------

INTERVAL TESTED <b>3142-3163.5M</b>	BHP SURVEY DEPTH (FT.)	GAS PRODUCED TO <input type="checkbox"/> PIPELINE <input checked="" type="checkbox"/> FLARE	GAS METER RUN SIZE <b>5.761 (INS)</b>	DIFF. RANGE (INS. H <sub>2</sub> O) <b>0-100</b>	STATIC PRESSURE TAKEN <input type="checkbox"/> UPSTREAM <input checked="" type="checkbox"/> DOWNSTREAM
--	------------------------	--	--	---	---

TIME		WELLHEAD DATA			DOWNHOLE DATA		FLOW CONTROL		GAS METERING				OIL OR CONDENSATE METERING				WATER METERING			
DAY	FLOW OR SHUT-IN DURATION	TUBING PRESS.	TEMP.	CASING PRESS.	B H P	B H T	MAN. CHOKE	HEATER CHOKE	ORIFICE SIZE	STATIC PRESS.	DIFF. PRESS.	TEMP.	GAS GRAVITY (AIR=1)	# 1 TANK OR METER READING	# 1 OIL TEMP	OIL GRAVITY	W <sub>i</sub>	# 1 TANK OR METER READING	SALINITY	
24 HOUR CLOCK	(HOURS)	(PSIG)	(°F)	(PSIG)	(PSIG)	(°F)	(64TH) IN)	(64TH) IN)	(INS)	(PSIG)	( IN H <sub>2</sub> O )	(°F)	% H <sub>2</sub> S	# 2 TANK OR METER READING (INS OR BBL)	# 2 OIL TEMP (°F)	@ 60°F °API	BSW (%)	# 2 TANK OR METER READING (INS. OR BBL)	(%)	
1	26																			
	0335	10.05	235	73	2530	0.0	0	24												
2	26																			
	0340	10.14	213	71	2530	0.0	0	24												
3	26																			
	0345	10.22	207	70	2530	0.0	0	24												
4	26	CHANGED TO 16/64" ADJUSTABLE CHOKE																		
	0346	10.23	195	68	2410	0.0	0	16												
5	26																			
	0350	10.30	197	68	2420	0.0	0	16												
6	26																			
	0400	10.47	167	65	2420	0.0	0	16												
7	26																			
	0405	10.55	153	65	2420	0.0	0	16												
8	26																			
	0410	10.64	147	64	2420	0.0	0	16												
9	26																			
	0415	10.72	140	64	2420	0.0	0	16												
10	26																			
	0420	10.80	130	63	2420	0.0	0	16												
11	26																			
	0425	10.89	128	63	2420	0.0	0	16												
12	26																			
	0430	10.97	123	63	2420	0.0	0	16												
13	26																			
	0435	11.05	121	62	2420	0.0	0	16												
14	26	CHANGED TO 16/64" POSITIVE CHOKE																		
	0440	11.14	122	62	2420	0.0	0	16												
15	26																			
	0442	11.17	130	62	2410	0.0	0	16												
16	26																			
	0443	11.19	134	62	2410	0.0	0	16												
17	26																			
	0444	11.20	137	62	2410	0.0	0	16												

Computer Form Toppan (Hose)