



FIELD READINGS
SINGLE STAGE UNIT
OEC - 905-1-A

TEST NO. DST#4	WELL NAME OR NUMBER PELICAN #5	TEST UNIT DESCRIPTION 1440PSI 3PHASE SEPARATOR	DATE (DAY. MO. YR.) 27MAR86	PAGE 2	OF 3
--------------------------	--	--	---------------------------------------	------------------	----------------

CUSTOMER AMOCO AUSTRALIA PETROLEUM CO.	FIELD PELICAN	FORMATION SANDSTONE	OIL METER SIZE 0	METER RANGE (BBLs) ---
--	-------------------------	-------------------------------	----------------------------	----------------------------------

INTERVAL TESTED 3142-3163.5M	BHP SURVEY DEPTH (FT.)	GAS PRODUCED TO <input type="checkbox"/> PIPELINE <input checked="" type="checkbox"/> FLARE	GAS METER RUN SIZE 5.761 (INS)	DIFF. RANGE (INS. H ₂ O) 0-100	STATIC PRESSURE TAKEN <input type="checkbox"/> UPSTREAM <input checked="" type="checkbox"/> DOWNSTREAM
--	------------------------	--	--	---	---

TIME	WELLHEAD DATA				DOWNHOLE DATA				FLOW CONTROL		GAS METERING				OIL OR CONDENSATE METERING				WATER METERING		
	DAY	FLOW OR SHUT-IN DURATION	TUBING PRESS.	TEMP.	CASING PRESS.	BHP	BHT	MAN. CHOKE	HEATER CHOKE	ORIFICE SIZE	STATIC PRESS.	DIFF. PRESS.	TEMP.	GAS GRAVITY (AIR=1)	# 1 TANK OR METER READING	# 1 OIL TEMP	OIL GRAVITY	W _f	# 1 TANK OR METER READING	SALINITY	
24 HOUR CLOCK	(HOURS)	(PSIG)	(°F)	(PSIG)	(PSIG)	(°F)	(64TH IN)	(64TH IN)	(INS)	(PSIG)	(IN H ₂ O)	(°F)	% H ₂ S	# 2 TANK OR METER READING (INS OR BBL)	# 2 OIL TEMP (°F)	@ 60°F °API	BSW (%)	# 2 TANK OR METER READING (INS. OR BBL)	(%)		
1	27																				
0633	0.04	180	58	1450	0.0	0	16														
2	27																				
0634	0.06	160	58	1460	0.0	0	16														
3	27																				
0635	0.08	140	58	1460	0.0	0	16														
4	27																				
0636	0.09	110	58	1460	0.0	0	16														
5	27																				
0637	0.11	98	58	1460	0.0	0	16														
6	27																				
0638	0.13	60	58	1470	0.0	0	16														
7	27																				
0639	0.14	40	58	1470	0.0	0	16														
8	27	CHANGED TO 24/64" ADJUSTABLE CHOKE																			
0640	0.16	180	58	1470	0.0	0	24														
9	27																				
0641	0.18	250	60	1470	0.0	0	24														
10	27																				
0642	0.19	285	60	1470	0.0	0	24														
11	27																				
0643	0.21	280	62	1480	0.0	0	24														
12	27																				
0644	0.23	280	62	1480	0.0	0	24														
13	27																				
0645	0.24	273	62	1480	0.0	0	24														
14	27																				
0650	0.33	260	62	1480	0.0	0	24														
15	27	CHANGED TO 108/64" ADJUSTABLE CHOKE																			
0655	0.41	150	62	1480	0.0	0	108														
16	27	CHANGED TO 128/64" POSITIVE CHOKE																			
0700	0.49	74	61	1480	0.0	0	128														
17	27	FLOW DIVERTED TO THE SEPARATOR																			
0705	0.58	55	60	1480	0.0	0	128														