



FIELD READINGS
SINGLE STAGE UNIT
OEC - 905-1-A

446325

TEST NO. DST#5	WELL NAME OR NUMBER PELICAN #5	TEST UNIT DESCRIPTION 1440PSI 3PHASE SEPARATOR	DATE (DAY, MO. YR.) 30MAR86	PAGE 1	OF 15
--------------------------	--	--	---------------------------------------	------------------	-----------------

CUSTOMER AMOCO AUSTRALIA PETROLEUM.CO.	FIELD PELICAN	FORMATION SANDSTONE	OIL METER SIZE 0	METER RANGE (BBLs) ---
--	-------------------------	-------------------------------	----------------------------	---------------------------

INTERVAL TESTED 2868-2884M	BHP SURVEY DEPTH (FT.)	GAS PRODUCED TO <input type="checkbox"/> PIPELINE <input checked="" type="checkbox"/> FLARE	GAS METER RUN SIZE 5.761 (INS)	DIFF. RANGE (INS. H ₂ O) 0-100	STATIC PRESSURE TAKEN <input type="checkbox"/> UPSTREAM <input checked="" type="checkbox"/> DOWNSTREAM
--------------------------------------	------------------------	--	--	---	---

TIME		WELLHEAD DATA			DOWNHOLE DATA		FLOW CONTROL		GAS METERING				OIL OR CONDENSATE METERING				WATER METERING			
DAY	FLOW OR SHUT-IN DURATION	TUBING PRESS.	TEMP.	CASING PRESS.	BHP	BHT	MAN. CHOKE	HEATER CHOKE	ORIFICE SIZE	STATIC PRESS.	DIFF. PRESS.	TEMP.	GAS GRAVITY (AIR=1)	# 1 TANK OR METER READING	# 1 OIL TEMP	OIL GRAVITY	W _f	# 1 TANK OR METER READING	SALINITY	
24 HOUR CLOCK	(HOURS)	(PSIG)	(°F)	(PSIG)	(PSIG)	(°F)	(64TH IN)	(64TH IN)	(INS)	(PSIG)	(IN H ₂ O)	(°F)	% H ₂ S	# 2 TANK OR METER READING (INS OR BBL)	# 2 OIL TEMP (°F)	@ 60°F °API	BSW (%)	# 2 TANK OR METER READING (INS. OR BBL)	(%)	
1	30	TEST STRING AND TUBING CONVEYED PERFORATING GUNS																		1
	0525	0.00																		
2	30	RAN IN THE HOLE																		2
	0525	0.00																		
3	30	TEST STRING DISPLACED WITH NITROGEN																		3
	0525	0.00																		
4	30	BOP RAMS CLOSED																		4
	0525	0.00																		
5	30	PRESSURED UP ANNULUS TO OPEN LPR-N TEST VALVE																		5
	0527	0.03	1350	56	1480	0.0	0	0												
6	30	BLED DOWN WELLHEAD PRESSURE																		6
	0532	0.11	1350	56	1480	0.0	0	0												
7	30	INCREASED ANNULUS PRESSURE TO ACTIVATE																		7
	0543	0.29	1350	56	2200	0.0	0	0												
8	30	PERFORATING GUNS																		8
	0543	0.29	1350	56	2200	0.0	0	0												
9	30																			9
	0544	0.31	1350	56	2200	0.0	0	0												
10	30																			10
	0545	0.33	1350	56	2400	0.0	0	0												
11	30																			11
	0546	0.34	1360	56	2500	0.0	0	0												
12	30																			12
	0547	0.36	1370	56	2500	0.0	0	0												
13	30																			13
	0548	0.38	1390	56	2500	0.0	0	0												
14	30																			14
	0550	0.41	1402	58	2500	0.0	0	0												
15	30																			15
	0551	0.43	1420	58	2500	0.0	0	0												
16	30																			16
	0552	0.44	1425	59	2500	0.0	0	0												
17	30																			17
	0553	0.46	1430	59	2500	0.0	0	0												

Computer - Forns Toppan Norge