

COMPANY AMOCO AUSTRALIA		WELL NAME & No.	FIELQ	COUNTRY TASMANIA	SPUD DATE	RIG RELEASE	DRILLING PARAMETERS									
BHA No.	BIT No.	BOTTOM HOLE ASSEMBLY				WOB	RPM	DEPTH IN	DEPTH OUT	ANGLE BELOW	ANGLE ABOVE					
17	18	8 1/2"	FS	6 1/2" Monel	20-6 1/2" DC	5" HWDP	Jar	14-5" HWDP	10/20	100/140	11463	11493	5.76°	5.76°		
18	19	8 1/2"	JS	FS	6 1/2" Monel	20-6 1/2" DC	5" HWDP	Jar	14-5" HWDP	45	100	11493	11966	5.0°	5.76°	
19	20RR19 CIRREP	8 1/2"	FS	6 1/2" Monel	20-6 1/2" DC	5" HWDP	Jar	14-5" HWDP	WIPER TRIP							
20	22	8 1/2"	JS	FS	6 1/2" Monel	20-6 1/2" DC	5" HWDP	Jar	14-5" HWDP	WIPER TRIP						
21	23	8 1/2"	FS	6 1/2" Monel	20-6 1/2" DC	5" HWDP	Jar	13-5" HWDP	DRESS CMT TO T.O.L.							
22	24	6"	FS	24-4-3/4" DC	Jar	81-3 1/2" DP	XO		DRILL CMT TO FLOAT SHOE							
23	25	6"	FS	24-4-3/4" DC	Jar	14-3 1/2" HWDP	81-3 1/2" DP	XO	15/20	60	11966	12028	5.0°	5.0°		
24	26	6"	4-3/4" DC	4-3/4" DC	22-4-3/4" DC	Jar	14-3 1/2" HWDP	81-3 1/2" DP	XO	20	68	12028	12262	5.75°	5.0°	
25	27	6"	Turbine Sub	Circ	4-3/4" DC	23-4-3/4" DC	Jar	8-3 1/2" HWDP	81-3 1/2" DP	XO	5/10	50	12262	12293	5.75°	5.75°
26	28	6"	FS	4-3/4" DC	4-3/4" DC	22-4-3/4" DC	Jar	8-3 1/2" HWDP	87-3 1/2" DP	XO	20	70	12293	12492	5.75°	5.75°
27	29RR27	6"	Turbine Sub	Circ	4-3/4" DC	23-4-3/4" DC	Jar	8-3 1/2" HWDP	87-3 1/2" DP	XO	6/10	50	12492	13363	7.0°	5.75°
28	30	6"	Pony DC	4-3/4" Monel	24-4-3/4" DC	Jar	8-3 1/2" HWDP	114-3 1/2" DP	XO	10/15	105	13363	13764	7.0°	7.0°	
29	31	6"	Turbine Sub	Circ	4-3/4" Monel	24-4-3/4" DC	Jar	8-3 1/2" HWDP	114-3 1/2" DP	XO	8/10	50	13764	14000		7.0°
30	32	6"	BS	4-3/4" DC	23-4-3/4" DC	Jar	8-3 1/2" HWDP	114-3 1/2" DP	XO	WIPER TRIP						

450375