

TELEX MESSAGE TELEX MESSAGE TELEX MESSAGE

TELEX MESSAGE TELEX MESSAGE TELEX MESSAGE

450516

SST: CLR TO CRMY WHT, MED-GRN, M TO W SRT, SR, SILIC CMT TR DOL CMT.

CLST: MED BRN/GY, BLKY TO SUB-FIS, FIRM, GRDS TO SLST. MOD CARB, ARG, MICMIC, FIRM.

COAL: 3383.3-3385.5M, 3390.7-3390.9M, BLK, FIRM TO HD, BLKY TO SUB-FIS TO FIS WITH COMM CONCH FRAC SURFACE. MICMIC, MICRO-LAM, VIT LUSTRE.

GAS SUMMARY

BACKGROUND GAS: 50 - 100 UNITS (1-2%)
 COMPOSITION C1 - C5

MAXIMUM GAS: DEPTH 3392M (11128 FT), 1290 UNITS (25.8%)
 COMPOSITION C1 = 124659, C2 = 19933, C3 = 9121, C4 = 1359, NC4 = 2329, C5 = 1034

TRIP GAS: NIL

CONNECTION GAS: 365 U AT 3304M, 355 U AT 3314M, 10 U AT 3323M,
 15 U AT 3351M, 420 U AT 3399M.

WL 21.3
 BL 10.4
 CL 0.52

RATES OF PENETRATION

MAXIMUM ROP: DEPTH 3405M (11171FT), 24 M/HR (79 FT/HR)
 MINIMUM ROP: DEPTH 3374M (11069FT), 2.7M/HR (8.8FT/HR)
 AVERAGE ROP: 5.0 M/HR (16.5 FT/HR)

PRESSURE PARAMETERS

DXC, RANGE: 1.02 - 1.60

TEMP OUT: 51 DEG C TEMP IN: 49 DEG C

MUD WT. IN: 12.4 PPG MUD WT. OUT: 12.4 PPG ECD: PPG

EST PORE PRESSURE: 12.0 PPG EMW EST FRACTURE PRESSURE: 18.6 PPG EMW

REGARDS,
 C.W. WARING
 AMOCO AUSTRALIA PETROLEUM COMPANY

AAAA*
 TASROK AA58276