

SAGE TELEX MESSAGE TELEX MESSAGE TELEX MESSAGE TELEX MESSAGE TELEX MESSAGE

TELEX MESSAGE TELEX MESSAGE TELEX MESSAGE TELEX MESSAGE TELEX MESSAGE

450623

81

86-04-10 1011 ST *
TASROK AA58276
STBY BCAST 176199 CLG

DEPARTMENT OF MINES
RECEIVED/SENT
10 APR 1986
10.20 AM/PM
OPERATOR *[Signature]*

10 APRIL, 1986

DRILLING WIRE - PELICAN NO. 5 - BASS BASIN, AUSTRALIA
=====

AMOCO CORPORATION - CHICAGO
ATTN: T.D. STACY MC 4502
B.G. NEWTON MC 4703
CH-AUP-126-T-420.61-CWW/SCB/CDC/GMK

TX: 020/234991785+

BUREAU OF MINERAL RESOURCES
THE DIRECTOR
ATTN: J. WHITE

TX: AA62109

TASMANIAN DEPARTMENT OF MINES
ATTN: H. MURCHIE

TX: AA58276

MISC-AUP-458-T-420.61-CWW/SCB/CDC/GMK

CC: AMOCO AUSTRALIA PETROLEUM COMPANY
- HOBART ATTN: C.D. CORNELL
ABB-AUP-096-T-420.61-CWW/SCB/CDC/GMK

TX: AA58162

DATE : 10 APRIL, 1986
REPORT NO. : 106
DAYS FROM SPUD : 103
PBTD : 2847 METERS (9341 FT)
PROGRESS : 0
MUD PROPERTIES : MW -9.2, VIS - 43, API FL -7.9
LAST CASING : 5' AT 4065.2 METERS (13,337 FT)
DAILY COST (USD) : 102,338 CUM. COST : 13,114,840
PRESENT OPERATION : PICKING UP DST NO 6 TOOLS.
OPERATIONS SUMMARY : CONTINUE TO MONITOR WELL, TUBING PRESSURE
-D-PSI, FINAL FLUID LEVEL 163.5 M (5364 FT) AT
10:10 HRS, LAST HR INFLUX RATE 28.5 M (93.5
FT) HR. CLOSE LPR-N VALVE, LAY DOWN
SCHLUMBERGER PLT AND LUBRICATOR, LAY DOWN 15.2
M (50 FT) SLINGS. REVERSE CIRCULATE WITH 85
BBLB MUD, CATCH SAMPLE, GAS CUT MUD/WATER CUT,
FLUSH OUT OTIS SURFACE EQUIPMENT. RELEASE
PACKER LAY DOWN SURFACE TREE, CIRCULATE
CONVENTIONALLY WHILE RIGGING DOWN SURFACE
EQUIPMENT. (MAX GAS 136 UNITS). POH WITH
LANDING STRING, LAY DOWN SUBSEA LUBRICATOR
VALVE, POH WITH TUBING STRING, LAY DOWN TEST
TOOLS, RIG UP SCHLUMBERGER, RIH AND SET
9-5/8" BRIDGE PLUG AT 2847 M (9341 FT) POH
WITH WIRELINE, PRESSURE TEST BRIDGE PLUG TO
1100 PSI (OK) RIG DOWN SCHLUMBERGER, SERVICE
DST TOOLS, PICK-UP DST NO 6 TEST TOOLS.

REGARDS
C.W. WARING
AMOCO AUSTRALIA PETROLEUM COMPANY