

Enclosure 12 C
 Schlumberger
 SIDEWALL CORES SUITE #4
 CSU Field Log

COMPANY: AMOCO AUSTRALIA PETROLEUM CO.
 WELL: PELICAN #5
 FIELD: TASMANIA
 STATE: D.M.EPOCH
 RIG: AUSTRALIA
 NATION: SHOT POINT 240
 LOCATION: LINE TNK4-87
 LATITUDE: 40 20' 43.259"S
 LONGITUDE: 145 51' 49.971"E

PERMANENT DATUM: MSL
 ELEVATIONS:-
 ELEV. OF PERM. DATUM: 0.0 M
 LOG MEASURED FROM: KB
 DRI. MEASURED FROM: KB
 DRI. MEASURED FROM: KB

PROGRAM
 TAPE NO:
 LDI CNU AMS
 ISF BHC MSFL
 HDT
 MSS
 RFT-GR

DATE: 5 MAR 86
 RUN NO: 3

DEPTH-DRILLER: 4867.0 M
 DEPTH-LOGGER: 4867.5 M
 BTM. LOG INTERVAL: 4855.0 M
 TOP LOG INTERVAL: 3853.0 M
 CASING-DRILLER: 1750.8 M
 CASING-LOGGER: 1750.0 M
 CASING LOG INTERVAL: 13 3/8 IN.
 HEIGHT: 72.0000 LB/F 53.5000 LB/F 29.0000 LB/F
 BIT SIZE: 17 1/8 IN. 12 1/4 IN. 6 IN.
 DEPTH: 1776.0 M 4867.0 M

TYPE FLUID IN HOLE: FRESH WATER LIME
 DENSITY: 15.80 LB/G
 VISCOSITY: 50.0 S
 PH: 12.0
 FLUID LOSS: 4.9 C3
 SOURCE OF SAMPLE: FLOWLINE
 RM: .559 DHMM AT 65.0 DEGF
 RMF: .305 DHMM AT 71.0 DEGF
 RMC: .867 DHMM AT 71.0 DEGF
 SOURCE RMF/RMC: PRESS /PRESS
 RM AT BHT: .112 DHMM AT 352. DEGF
 RMF AT BHT: .066 DHMM AT 352. DEGF
 RMC AT BHT: .188 DHMM AT 352. DEGF

TIME CIRC. STOPPED: 0430/03
 TIME LOGGER ON BTM.: 0820/05

MAX. REC. TEMP: 352.0 DEGF

LOGGING UNIT NO: 822
 LOGGING UNIT LOC: VEA
 RECORDED BY: WINSLOE
 WITNESSED BY: G.HEEMINK

REMARKS:

EQUIPMENT NUMBERS-
 CST-V 2405 CST-V 1486 SHM-AA 1778 GPC-A 619

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

CP 27.61F FILE 0 05-MAR-86 13:11

Schlumberger CST RUN #1
 CSU Field Log
 CP 27.61F FILE 0 05-MAR-86 09:37

SHOT SUMMARY LISTING PERFORMED 05-MAR-86 09:37

SHOT	STATUS	DEPTH	TENSION
1	FIRE	4255.06	187.0
2	FIRE	4246.92	554.0
3	FIRE	4216.09	244.5
4	FIRE	4162.00	175.7
5	FIRE	4120.12	192.5
6	FIRE	4106.89	215.5
7	FIRE	4076.28	478.0
8	FIRE	4048.59	179.2
9	FIRE	4013.55	210.2
10	FIRE	3998.26	202.1
11	FIRE	3976.46	55.37
12	FIRE	3928.55	169.0
13	FIRE	3903.81	343.2
14	FIRE	3891.51	140.6
15	FIRE	3836.38	217.8
16	FIRE	3774.45	169.2
17	FIRE	3716.53	722.5
18	FIRE	3697.02	70.37
19	FIRE	3684.00	149.2
20	FIRE	3667.53	50.65
21	FIRE	3653.09	165.7

DEPTH UNITS : METE BIT SIZE : 6.000 IN
 RING TYPE : NONE BULLET TYPE : COMB
 POWDER LOAD : 8.00 G POWDER TYPE : AHT

Schlumberger CST RUN #2
 CSU Field Log

SHOT SUMMARY LISTING PERFORMED 05-MAR-86 12:07

SHOT	STATUS	DEPTH	TENSION
1	FIRE	4236.51	157.8
2	FIRE	4213.24	111.8
3	FIRE	4203.73	122.1
4	FIRE	4170.64	198.7
5	FIRE	4154.59	515.0
6	FIRE	4130.04	89.06
7	FIRE	4112.98	280.7
8	FIRE	4087.70	148.5
9	FIRE	4085.01	65.25
10	FIRE	4071.57	413.2
11	FIRE	4056.92	119.6
12	FIRE	4034.39	84.50
13	FIRE	4016.14	145.8
14	FIRE	4010.32	150.5
15	FIRE	4005.06	106.9
16	FIRE	3995.60	170.6
17	FIRE	3989.63	245.6
18	FIRE	3940.97	151.0
19	FIRE	3937.32	46.87
20	FIRE	3910.55	145.7
21	FIRE	3907.08	215.5

DEPTH UNITS : METE BIT SIZE : 6.000 IN
 RING TYPE : NONE BULLET TYPE : COMB
 POWDER LOAD : 8.00 G POWDER TYPE : AHT

Schlumberger CST RUN #3
 CSU Field Log

SHOT SUMMARY LISTING PERFORMED 05-MAR-86 15:51

SHOT	STATUS	DEPTH	TENSION
1	FIRE	4106.56	132.2
2	FIRE	4012.49	54.62
3	FIRE	4005.03	409.7
4	FIRE	3995.05	122.3
5	FIRE	3902.96	100.7
6	FIRE	3900.52	125.5
7	FIRE	3895.57	130.5
8	FIRE	3875.01	159.2
9	FIRE	3846.06	137.5
10	FIRE	3810.57	172.8
11	FIRE	3778.07	170.1
12	FIRE	3741.25	80.50
13	FIRE	3726.05	220.6
14	FIRE	3710.08	157.7
15	FIRE	3700.03	178.7
16	FIRE	3692.55	394.0
17	FIRE	3688.09	435.5
18	FIRE	3679.57	201.1
19	FIRE	3673.08	601.5
20	FIRE	3663.58	221.5
21	FIRE	3660.04	299.5

DEPTH UNITS : METE BIT SIZE : 6.000 IN
 RING TYPE : NONE BULLET TYPE : COMB
 POWDER LOAD : 8.00 G POWDER TYPE : AHT

