APPEA JV

CSU

CSU

COMPANY: AMOCO AUSTRALIA		
WELL: DATE DRILLED: 26, 1		OTHER SERVICES:
FIELD: COUNTY:		
STATE: TERRITORY: AUSTRALIA		
LOCATION:	PAD:	
Other Services: CSG GR CAL SP LDT CNL DLL MSFL		
PERMANENT DATUM: M.S.L.	ELEVATIONS:	
LOG MEASURED FROM: KB	KB: 4117'	
DRILLING MEASURED FROM: KB	DF: 4117'	
	GL: 4088'	
Rig: RIG#2		
Run No.		
DEPTH-DRILLER: 9500.0		
DEPTH-LOGGER: 9500.0		
BTM. LOG INTERVAL: 9500.0		
TOP LOG INTERVAL: 8000.0		
CASING-DRILLER: 13 3/8" @ 1500'		
CASING-LOGGER:		
BIT SIZE: 12 1/4" @ 1500'	8 1/2" @ 9500'	
TYPE FLUID IN HOLE:	LSND	
DENSITY:	10.0	
VISCOSITY:	45	
PH:	9.5	
FLUID LOSS:	4.8 cc	
SOURCE OF SAMPLE:	CIRC	
RM @ MEAS TEMP:	0.180 @ 60.0 DF	
RMF @ MEAS TEMP:	0.160 @ 60.0 DF	
RMC @ MEAS TEMP:	0.240 @ 60.0 DF	
RM @ BHT:	0.120 @ 180 DF	
TIME CIRC:	4 HRS	
TIME LOGGER ON BTM:	1500	
MAX. REC. TEMP:	180.0 DF	
EQUIP. LOCATION:	DARW	
RECORDED BY:	SCOTT	
WITNESSED BY:	C. KELLY	

REMARKS:
RUN 1 WITH TOOLPOSITION STANDOFF ON BOW
RUN 2 WITH TOOLPOSITION STANDOFF ON BOW
CNL RUN WITH 4.5" SLIM HOLE

CASING RECORDS:		
13 3/8 @ 1500'	9 5/8 @ 5000	7" @ 9500'
20" @ 1500'	13 3/8 @ 1500'	

TYPE FLUID IN HOLE:	*PRIMARY/SEC OIL FILTRATE
DENSITY:	10.0
VISCOSITY:	45.0
PH:	9.5
FLUID LOSS:	4.8 cc
SOURCE OF SAMPLE:	CIRC
RM @ MEAS TEMP:	0.180 @ 60.0 DF
RMF @ MEAS TEMP:	0.160 @ 60.0 DF
RMC @ MEAS TEMP:	0.240 @ 60.0 DF
RM @ BHT:	0.120 @ 180 DF
TIME CIRC:	4 HRS
TIME LOGGER ON BTM:	1500
MAX. REC. TEMP:	180.0 DF
EQUIP. LOCATION:	DARW
RECORDED BY:	SCOTT
WITNESSED BY:	C. KELLY

REMARKS:
RUN 1 WITH TOOLPOSITION STANDOFF ON BOW
RUN 2 WITH TOOLPOSITION STANDOFF ON BOW
CNL RUN WITH 4.5" SLIM HOLE

TREATMENT RECORDS:

9.5 PPG MUD	9.5 PPG MUD	9.5 PPG MUD
13 3/8 @ 1500'	9 5/8 @ 5000	7" @ 9500'

*A 4" PERFORATED GUN WAS USED ACROSS THE PERFORATED ZONE FOR ACQUISITION. THE PERFORATED ZONE WAS ACQUIRED WITH A 4" GUN