ENCL. 8.

Schlumberger

OR. 03584.

CYBERDIP 4PAD LOGIC

CSU Field Log

4C0129

COMPANY: AMOCO AUSTRALIA
WELL: CAPE SORELL NO. 1
FIELD: WILDCAT
STATE: TASMANIA
NATION: AUSTRALIA
LOCATION: SOUTHWEST TASMANIA
SEC: TWP: RGE:
LATITUDE: 042 08 09.54 S
LONGITUDE: 145 01 47.06 E

PERMANENT DATUM: M.S.L.
ELEV. OF PERM. DATUM:
LOG MEASURED FROM: KB
72.0 ' ABOVE PERM. DATUM
DRLG. MEASURED FROM: KB

ELEVATIONS-
KB: 72.0 '
DF: 71.0 '
GL: -309.0 '

OTHER SERVICES-
DIL-SLS-GR
HDT
CST
RFT

PROGRAM TAPE NO:
22.1
SERVICE ORDER NO:
SEA 07 07

DATE: 5 SEP -499
RUN NO: 4

DEPTH-DRILLER: 11578.0 '
DEPTH-LOGGER: 11560.0 '
BTM. LOG INTERVAL: 11558.0 '
TOP LOG INTERVAL: 8998.0 '

CASING-DRILLER:	9002 '	4144 '	9002 '
CASING-LOGGER:	1393 '	4140 '	8998 '
CASING:	20	13.37	9.6
WEIGHT:	133.0 LB/F	68.00 LB/F	47.000 LB/F
BIT SIZE:	30	17.5	8.5
DEPTH:	4161 '	9033 '	11578 '

TYPE FLUID IN HOLE: FRESHWATER GEL
DENSITY: 9.6 LB/G
VISCOSITY: 49.0 S
PH: 10.0
FLUID LOSS: 6.0 C3
SOURCE OF SAMPLE: FLOWLINE
RM: 1.670 OHMM AT 60.0 DEGF
RMF: 1.290 OHMM AT 60.0 DEGF
RMC: 1.950 OHMM AT 60.0 DEGF
SOURCE RMF/RMC: PRESS /PRESS
RM AT BHT: 0.480 OHMM AT 226. DEGF
RMF AT BHT: 0.370 OHMM AT 226. DEGF
RMC AT BHT: 0.560 OHMM AT 226. DEGF

TIME CIRC. STOPPED: 2000
TIME LOGGER ON BTM.: 0930

MAX. REC. TEMP: 226.0 DEGF

LOGGING UNIT NO: 33
LOGGING UNIT LOC: SEA
RECORDED BY: H GOH
WITNESSED BY: W BRYANT

5 cm

REMARKS:

EQUIPMENT NUMBERS-

HDE F 736 HDS F 1945 HDM LB 711

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

FILE
0