OR-0358A

ENCL. 31

Schlumberger

TEMPERATURE LOG SCALE: 1/200 & 1/500

CSU Field Log

460153

COMPANY: AMOCO AUSTRALIA
WELL: CAPE SORELL NO. 1
FIELD: WILDCAT
STATE: TASMANIA
NATION: AUSTRALIA
LOCATION: SOUTHWEST TASMANIA
SEC: TWP: RGE:
LATITUDE: 042 08 09.54 S
LONGITUDE: 145 01 47.06 E
PERMANENT DATUM: M.S.L.
ELEV. OF PERM. DATUM:
LOG MEASURED FROM: KB
72.0' ABOVE PERM. DATUM
DRLG. MEASURED FROM: KB

ELEVATIONS-
KB: 72.0'
DF: 71.0'
GL: -309.0'

OTHER SERVICES-

PROGRAM TAPE NO: 20.2
SERVICE ORDER NO: SEA 07 07

DATE: 25 JUL 1982
RUN NO: 1

DEPTH-DRILLER:	4161.0'	
DEPTH-LOGGER:	4042.0'	
BTM. LOG INTERVAL:	4042.0'	
TOP LOG INTERVAL:	350.0'	
CASING-DRILLER:	693'	1393'
CASING-LOGGER:	693'	1392'
CASING:	30	20
WEIGHT:	310.0 LB/F	133.0 LB/F
BIT SIZE:	33	17.5
DEPTH:	1440'	4161'

TYPE FLUID IN HOLE:	FRESHWATER GEL
DENSITY:	8.9 LB/G
VISCOSITY:	88.0 S
PH:	10.0
FLUID LOSS:	9.0 C3
SOURCE OF SAMPLE:	FLOWLINE
RM:	1.420 OHMM AT 56.0 DF
RMF:	1.290 OHMM AT 56.0 DF
RMC:	1.580 OHMM AT 56.0 DF
SOURCE RMF/RMC:	PRESS /PRESS
RM AT BHT:	0.662 OHM AT 128. DF
RMF AT BHT:	0.602 OHM AT 128. DF
RMC AT BHT:	0.737 OHM AT 128. DF
TIME CIRC. STOPPED:	231800
TIME LOGGER ON BTM.:	0645
MAX. REC. TEMP:	128.0 DF
LOGGING UNIT NO:	33
LOGGING UNIT LOC:	SEA
RECORDED BY:	H GOH
WITNESSED BY:	D RENFOW

REMARKS:

REPEAT SECTION RAN HALF AN HOUR AFTER MAIN LOG
MAXIMUM TEMPERATURE RECORDED ON LOG EQUALLED TO TEMPERATURE
RECORDED BY DOWNHOLE THERMOMETERS

EQUIPMENT NUMBERS-

PPU A 909 HTU B 909 HTS B 1996

5 cm

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS AND WE CANNOT, AND DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE.

FILE
101

PARAMETERS

NAME	VALUE	UNIT	NAME	VALUE	UNIT
DO	0.0		BHS	OPEN	
FSIZ	6	IN	BS	17.50	IN

SENSOR MEASURE POINT TO TENSION REFERENCE POINT

CCL	.0	FEET	TENS	.0	FEET
TEMP	-7.7	FEET	A1P	-7.7	FEET
A2P	-7.7	FEET	A3P	-7.7	FEET
A4P	-7.7	FEET	A5P	-7.7	FEET
A6P	-7.7	FEET	A8P	-7.7	FEET
A10P	-7.7	FEET	A12P	-7.7	FEET
A13P	-7.7	FEET	A14P	-7.7	FEET
C0P	-7.7	FEET	C1P	-7.7	FEET
C2P	-7.7	FEET	C3P	-7.7	FEET

-19.00 CCL ( ) 1.000	60.00 TEMP(DF) 110.0
0.0 TEMP(DF) 200.0	5000. TENS(LB) 0.0

2
FILE