

* 19/ 8/82

CAPE SORELL # 1 e>EE' *

* DEPTH	RPM	WOB	ROP	MUD-WGT	FLOW	POISS	OVERB	DWCOR	DXCOM	DXEXP		PF	ECD	FRAC	POROS
* METERS		TONS	MM/H	KG/L	L/MN	*	*	*	*	*		EQUIVALENT	DENSITY		%
* 800.00	61	13.9	275.5	0.60	587	.29	17.40	1.0055	.56	1.00	PERMEABLE	8.80	9.30	11.29	49
* 804.00	71	14.5	300.2	0.54	587	.29	17.40	1.0050	.50	1.00	"	8.80	9.24	11.29	47
* 806.21	67	15.2	298.0	0.27	587	.29	17.40	1.0059	.59	1.00	"	8.80	8.97	11.29	45
* 810.19	48	17.9	264.7	0.60	587	.29	17.40	1.0062	.54	1.00	"	8.80	9.30	11.30	51
* 815.67	69	13.6	287.2	0.60	587	.29	17.40	1.0066	.57	1.00	"	8.80	9.29	11.30	40
* 821.89	68	18.9	603.3	0.60	597	.29	17.40	1.0070	.44	1.00	"	8.80	9.31	11.31	61
* 825.97	70	14.2	420.1	0.60	587	.29	17.40	1.0073	.50	1.00	"	8.80	9.20	11.32	56
* 830.00	73	16.7	178.7	0.68	591	.29	17.40	1.0076	.71	1.00	UNDER COMPACTED	11.56	9.37	13.27	10
* 836.37	61	15.6	33.96	0.60	584	.29	17.40	1.0080	1.04	1.00	NORMAL	8.80	9.27	11.33	10
* 845.68	51	18.4	99.82	0.60	573	.29	17.41	1.0086	.79	1.00	UNDER COMPACTED	10.70	9.23	12.73	10
* 856.37	64	22.2	107.9	0.60	582	.30	17.41	1.0093	.87	1.00	"	10.02	9.25	12.21	10
* 875.34	63	19.3	112.7	0.60	577	.30	17.41	1.0106	.83	1.00	"	10.45	9.22	12.53	10
* 880.04	67	21.7	118.5	0.60	578	.30	17.42	1.0109	.85	1.00	"	10.10	9.22	12.35	10
* 885.65	64	21.2	44.30	0.60	578	.30	17.42	1.0113	1.07	1.01	NORMAL	8.80	9.22	11.30	10
* 890.21	67	19.3	34.99	0.60	577	.30	17.42	1.0116	1.11	1.01	"	8.80	9.21	11.39	10
* 900.19	65	21.6	118.8	0.60	577	.30	17.42	1.0122	.84	1.01	UNDER COMPACTED	10.29	9.20	12.44	10
* 906.14	66	14.0	141.7	0.60	602	.30	17.42	1.0126	.72	1.01	"	11.53	9.25	13.31	10
* 911.10	64	19.2	84.63	0.60	606	.30	17.42	1.0129	.89	1.01	"	9.84	9.26	12.14	10
* 915.57	64	16.1	109.3	0.60	601	.30	17.43	1.0132	.79	1.01	"	10.79	9.25	12.81	10
* 920.68	66	21.1	315.1	0.60	607	.30	17.43	1.0136	.60	1.01	PERMEABLE	8.80	9.25	11.42	45
* 925.35	67	13.3	22.89	0.60	594	.30	17.43	1.0139	1.11	1.01	NORMAL	8.80	9.22	11.43	10
* 930.20	66	19.6	238.0	0.60	591	.31	17.43	1.0142	.66	1.01	PERMEABLE	8.80	9.21	11.43	39
* 935.34	65	17.0	352.5	0.60	587	.31	17.43	1.0145	.55	1.01	"	8.80	9.20	11.44	51
* 940.98	64	17.2	143.2	0.60	591	.31	17.43	1.0149	.75	1.01	UNDER COMPACTED	11.25	9.21	13.15	10
* 945.77	66	20.3	64.55	0.60	580	.31	17.44	1.0152	.90	1.01	NORMAL	8.80	9.20	11.45	10
* 950.89	67	15.6	100.7	0.60	606	.31	17.44	1.0155	.82	1.01	UNDER COMPACTED	10.58	9.23	12.69	10
* 955.20	71	14.5	22.81	0.60	596	.31	17.44	1.0158	1.15	1.01	NORMAL	8.80	9.21	11.46	10
* 960.26	65	20.5	89.47	0.60	587	.31	17.44	1.0161	.90	1.01	UNDER COMPACTED	9.75	9.19	12.12	10
* 965.84	62	21.5	226.9	0.60	587	.31	17.44	1.0165	.60	1.01	PERMEABLE	8.80	9.18	11.47	37
* 970.88	66	24.3	130.1	0.60	587	.31	17.44	1.0168	.85	1.01	UNDER COMPACTED	10.24	9.18	12.47	10
* 975.37	66	23.6	118.7	0.60	587	.31	17.44	1.0171	.87	1.01	"	10.09	9.18	12.37	10
* 980.89	64	25.0	120.9	0.60	592	.31	17.45	1.0174	.87	1.01	"	10.10	9.18	12.38	10
* 985.53	66	21.7	149.0	0.60	584	.31	17.45	1.0177	.80	1.01	"	10.83	9.17	12.89	10
* 990.13	64	22.2	66.19	0.60	596	.31	17.45	1.0180	.99	1.01	NORMAL	8.80	9.19	11.50	10
* 1000.07	67	25.3	18.84	0.60	592	.31	17.45	1.0187	1.36	1.01	"	8.80	9.17	11.51	10
* 1005.59	69	17.7	204.4	0.60	582	.31	17.45	1.0190	.69	1.01	PERMEABLE	8.80	9.15	11.51	36
* 1010.24	70	18.2	201.7	0.60	592	.31	17.46	1.0193	.70	1.02	"	8.80	9.17	11.52	35
* 1016.77	73	23.0	28.07	0.60	596	.31	17.46	1.0197	1.24	1.02	NORMAL	8.80	9.17	11.53	10
* 1020.59	74	23.7	50.18	0.60	602	.32	17.46	1.0200	1.11	1.02	"	8.80	9.18	11.53	10
* 1030.69	71	23.7	38.20	0.60	596	.32	17.46	1.0206	1.17	1.02	"	8.80	9.16	11.54	10
* 1035.10	69	27.9	26.78	0.60	596	.32	17.46	1.0209	1.31	1.02	"	8.80	9.16	11.54	10
* 1040.40	66	26.7	139.9	0.60	606	.32	17.46	1.0212	.85	1.02	UNDER COMPACTED	10.27	9.18	12.56	10
* 1045.51	65	23.7	101.6	0.60	596	.32	17.47	1.0215	.90	1.02	"	9.77	9.16	12.22	10
* 1050.86	65	24.6	58.91	0.60	596	.32	17.47	1.0218	1.05	1.02	NORMAL	8.80	9.15	11.56	10
* 1055.81	65	26.5	42.16	0.60	596	.32	17.47	1.0222	1.16	1.02	"	8.80	9.15	11.57	10
* 1065.14	65	26.6	26.77	0.60	596	.32	17.47	1.0227	1.28	1.02	"	8.80	9.15	11.58	10
* 1070.78	65	22.1	423.0	0.60	602	.32	17.47	1.0231	.54	1.02	PERMEABLE	8.80	9.15	11.58	52
* 1075.37	66	22.3	308.2	0.60	592	.32	17.48	1.0234	.62	1.02	"	8.80	9.13	11.59	44
* 1080.79	64	26.6	43.58	0.60	592	.32	17.48	1.0237	1.15	1.02	NORMAL	8.80	9.13	11.59	10
* 1085.37	62	25.6	46.47	0.60	592	.32	17.48	1.0240	1.11	1.02	"	8.80	9.13	11.60	10