

* GEOSERVICES

CAPE SORELL # 1

DATE : 16/ 8/82 *

* ON-LINE TDC

* BIT # 24 SMITH F3 BIT DIAMETER : 8.50 inch NOZZ 13/13/13

MUD RHEOLOGICAL PARAMETERS : PV = 20 YP = 10 GEL = 6 *

* Hr:mn	* MEASURED feet	* DEPTHS			* DRILLING PARAMETERS					* MUD PARAMETERS				* GAS				* OVERPRESSURE SURVEY				* ACCUMULATED ON BIT			
		VERTCL	LAGGED	ROP	WOB	RPM	TORQ	PRESS	FLOW	PIT	DENSITY	TEMPERATURE		RESISTIVITY		DCS	NORM	PF	ECD	FRAC	FEET	TIME	COST		
		feet	feet	ft/h	kibs	rpm	ftlb	psi	gpm	vol	in	out	in	out	in	out	unit	ppg	ppg	ppg	feet	Dhr	\$		
D * 7:35	9482.0	9471.9	9452.0	44.1	30.6	70	1900	1323	462	460	9.3	9.4	87.3	102.0	1.01	1.02	6	1.29	2.00	0.8	9.4	16.3	441.9	14.95	183
D * 7:38	9483.1	9473.0	9452.0	24.3	30.0	70	1900	1320	462	450	9.3	9.4	87.3	102.1	1.01	1.03	6	1.45	2.00	0.8	9.4	16.3	443.0	14.99	183
D * 7:39	9484.0	9473.9	9453.0	58.1	31.4	77	1900	1323	466	460	9.3	9.5	87.5	102.0	1.01	1.02	6	1.19	2.00	0.8	9.4	16.3	443.9	15.01	183
D * 7:41	9485.1	9473.9	9454.0	58.1	30.2	76	1900	1332	471	450	9.3	9.4	87.5	102.2	1.01	1.03	6	1.19	2.00	0.8	9.4	16.3	443.9	15.04	183
D * 7:43	9486.0	9475.0	9455.0	32.6	30.0	76	1900	1313	492	456	9.3	9.4	84.0	102.3	1.01	1.02	6	1.37	2.00	0.8	9.4	16.3	445.0	15.08	182
D * 7:53	9487.9	9477.3	9459.0	99.8	10.0	76	1500	1342	343	456	9.3	9.4	86.7	101.7	1.00	1.04	6	.83	2.00	0.8	9.4	16.3	447.3	15.09	182
D * 7:54	9488.6	9470.5	9459.0	86.0	36.0	80	2000	1304	338	454	9.3	9.4	86.7	101.2	1.00	1.03	6	1.06	2.00	0.8	9.4	16.3	448.5	15.11	181
D * 7:54	9489.1	9479.0	9459.0	47.1	35.6	70	2000	1374	341	450	9.3	9.3	86.1	101.3	1.00	1.03	6	1.30	2.00	0.8	9.4	16.3	449.0	15.12	181
D * 7:57	9490.1	9480.0	9461.0	20.7	33.1	70	2000	1276	326	440	9.3	9.3	87.2	101.6	1.00	1.01	6	1.52	2.00	0.8	9.4	16.3	450.0	15.16	181
D * 7:59	9491.2	9480.0	9462.0	20.7	30.6	77	2000	1290	326	430	9.3	9.3	87.3	101.6	1.00	1.02	6	1.52	2.00	0.8	9.4	16.3	450.0	15.20	181
D * 8:0	9492.2	9482.1	9462.0	45.4	30.5	77	2100	1285	326	436	9.3	9.3	87.2	101.8	1.00	1.01	6	1.26	2.00	0.8	9.4	16.3	452.1	15.22	181
D * 8:4	9493.1	9483.0	9465.0	14.0	32.0	76	3000	1257	326	434	9.3	9.3	87.2	103.5	1.00	1.00	6	1.62	2.00	0.8	9.4	16.3	453.0	15.28	181
D * 8:7	9494.1	9484.0	9466.0	22.6	35.4	70	3200	1243	326	432	9.3	9.4	87.3	103.5	1.00	1.01	6	1.49	2.00	0.8	9.4	16.3	454.0	15.33	181
D * 8:9	9495.1	9485.0	9466.0	35.3	31.2	76	3200	1252	325	430	9.3	9.4	87.1	103.2	1.00	1.01	6	1.35	2.00	0.8	9.4	16.3	455.0	15.35	181
D * 8:11	9496.4	9486.3	9467.0	31.9	34.5	76	3200	1230	325	420	9.3	9.4	87.3	102.9	1.00	1.01	7	1.36	2.00	0.8	9.4	16.3	456.3	15.39	181
D * 8:13	9497.2	9487.1	9468.0	25.6	33.2	77	3200	1252	326	420	9.4	9.4	87.3	102.5	1.00	1.01	6	1.42	2.00	0.8	9.4	16.3	457.1	15.43	181
D * 8:15	9498.0	9488.0	9468.0	29.9	34.2	70	3300	1243	326	420	9.4	9.3	87.4	103.0	1.01	1.01	6	1.30	2.00	0.8	9.4	16.3	458.0	15.46	181
D * 8:19	9499.4	9489.3	9469.0	18.2	34.0	76	3300	1243	325	426	9.4	9.3	87.5	102.6	1.01	1.02	6	1.53	2.00	0.8	9.4	16.3	459.3	15.53	181
D * 8:21	9500.4	9489.3	9469.0	18.2	29.1	77	3300	1240	326	426	9.4	9.4	87.5	102.0	1.00	1.03	7	1.53	2.00	0.8	9.4	16.3	459.3	15.57	181
D * 8:23	9501.0	9490.9	9469.0	28.2	30.0	76	3200	1240	325	424	9.4	9.4	87.5	103.6	1.00	1.02	6	1.30	2.00	0.8	9.4	16.3	460.9	15.59	180
D * 8:25	9502.1	9492.0	9470.0	27.7	36.5	77	3400	1267	330	424	9.4	9.4	87.5	103.3	1.01	1.01	6	1.45	2.00	0.8	9.4	16.3	462.0	15.63	180
T * 8:35	9502.3	9492.0	9475.0	-----	-----	35	1200	1351	334	416	9.3	9.4	87.6	103.0	1.00	1.02	7	-----	-----	-----	-----	-----	-----	-----	-----
T * 8:45	9502.3	9492.0	9479.0	-----	-----	20	1100	1313	334	412	9.3	9.5	87.8	105.1	1.01	1.01	6	-----	-----	-----	-----	-----	-----	-----	-----
T * 8:55	9502.3	9492.0	9484.0	-----	-----	24	1000	1356	334	404	9.3	9.5	88.3	104.9	1.01	1.01	6	-----	-----	-----	-----	-----	-----	-----	-----
T * 9:5	9502.3	9492.0	9486.0	-----	-----	0	-100	1295	334	390	9.3	9.4	88.9	105.5	1.01	1.01	6	-----	-----	-----	-----	-----	-----	-----	-----
T * 9:15	9502.3	9492.0	9491.0	-----	-----	39	1200	1379	330	392	9.3	9.4	89.3	105.4	1.01	1.01	6	-----	-----	-----	-----	-----	-----	-----	-----
T * 9:25	9502.3	9492.0	9496.0	-----	-----	40	1100	1320	330	384	9.3	9.5	89.6	105.1	1.00	1.01	7	-----	-----	-----	-----	-----	-----	-----	-----
T * 9:35	9502.3	9492.0	9499.0	-----	-----	27	1100	1351	333	382	9.3	9.5	90.0	105.6	1.01	1.01	7	-----	-----	-----	-----	-----	-----	-----	-----

466565