COMPANY: Golden Triangle NL
PROJECT: Main Creek
HOLE NUMBER: MC 52

Description			Core Recovery			RQD			Assays							
From	To		From	To	%	From	To	%	From	To	MgO	CaO	SiO_2	Fe_2O_3		
		abundant carbonate patches and cut by abundant white carbonate veins and streaks; minor fine -medium grained pyrite as grains and aggregates; ground conditions reasonable but broken in places by joint sets 30 and 45 CA; sharp contact with unit below 40 CA;							258.0	259.0	34.18	5.55	15.45	1.96		
									259.0	260.0	40.25	5.01	3.55	2.19		
									260.0	261.0	39.69	7.21	1.37	2.12		
									261.0	262.0	38.44	7.66	1.94	2.53		
									262.0	263.0	38.19	7.53	3.73	2.63		
									263.0	264.0	41.19	4.16	2.49	2.46		
									264.0	265.0	43.15	3.66	0.56	1.78		
									265.0	266.0	43.32	3.18	0.53	1.68		
328.0	376.0	**MAGNESITE:** massive white magnesite, extensively fractured and replaced by white-light gray crystalline magnesite and cut by numerous 1-20 mm veins crystalline and coarsely crystalline magnesite; minor schist bands and talcose dolomite sections; pyritic towards base; ground conditions good; **328.0-336.0 m:** light gray-white magnesite extensively replaced by light gray crystalline magnesite resulting in mottled appearance; rare pyrite, good ground conditions; **336.0-336.5 m:** darker gray magnesite, dolomitic and talcose; **336.5-349.2 m:** magnesite as for 328 m..... ; thin dolomite bands,with minor pyrite; principal joint set 30 CA; **349.0 m:** 600 mm. soft broken talcose dark gray schist; FW & HW contacts 50 CA; **349.6-364.5 m:** magnesite as for 328 m...; principal joint set 40 CA; ground conditions good; grades into unit below; **364.5-376.0 m:** magnesite, slightly more dolomitic than unit above and pyritic; 1-2% fine-medium grained euhedral pyrite as thin stringers, grains and aggregates, associated with crystalline magnesite patches and veins; principal joint set 30 CA; ground conditions generally excellent; sharp lower contact 60 CA;	328.0	376.0	100	328.0	337.8	100	266.0	267.0	42.97	4.04	0.24	1.79		
						337.8	342.4	90	267.0	268.0	40.65	5.07	2.68	2.68		
						342.4	346.8	90	268.0	269.0	39.25	6.61	4.48	2.63		
						346.8	351.4	85								
						351.4	356.0	95	272.1	273.0	40.09	6.69	1.51	1.77		
						356.0	365.2	100	273.0	274.0	40.01	7.54	0.81	1.50		
						365.2	369.9	95	274.0	275.0	39.52	8.36	0.36	1.36		
						369.9	376.0	100	275.0	276.0	38.48	9.24	0.85	1.31		
									276.0	277.0	25.85	22.06	4.37	1.66		
									277.0	278.0	28.76	18.79	3.97	1.41		
									278.0	279.0	35.91	12.09	1.24	1.52		
									279.0	280.0	39.36	7.03	2.11	1.73		
									280.0	281.0	38.42	8.37	2.00	1.78		
									281.0	282.0	38.54	7.04	3.18	2.10		
									282.0	283.2	38.40	5.65	5.07	2.50		
									284.8	286.0	39.98	4.67	3.10	3.01		
									286.0	287.9	41.02	4.40	2.09	2.70		
									290.0	291.0	39.78	4.50	5.51	2.75		
									291.0	292.0	42.06	3.67	2.00	2.41		
									292.0	293.0	40.20	3.83	5.35	3.04		
									293.0	294.0	43.49	1.69	1.95	2.84		
									294.0	295.8	43.11	2.37	2.08	2.47		
									297.5	299.0	42.15	3.49	2.45	2.05		
									299.0	300.0	42.47	3.03	2.60	1.70		
									300.0	301.0	42.97	3.71	0.78	1.48		
									301.0	302.0	43.20	3.05	1.49	1.45		
									302.0	303.0	44.20	2.61	0.16	1.38		
									303.0	304.0	43.87	3.03	<0.05	1.40		
									304.0	305.0	43.62	3.01	1.12	1.40		