




SHEET INDEX

|    |    |    |
|----|----|----|
| 1  | 2  | 3  |
| 4  | 5  | 6  |
| 7  | 8  | 9  |
| 10 | 11 | 12 |
| 13 | 14 | 15 |
| 16 | 17 | 18 |
| 19 | 20 | 21 |
| 22 | 23 | 24 |
| 25 | 26 | 27 |
| 28 | 29 | 30 |
| 31 | 32 | 33 |
| 34 | 35 | 36 |
| 37 | 38 | 39 |
| 40 | 41 | 42 |

CONTROL LINE INTERVAL VARIABLE  
 TRAVERSE INTERVAL 1/2 MILE  
 CONTOUR INTERVAL 20 FEET  
 BASE INTENSITY ARBITRARY  
 ALTITUDE 500 FEET MEAN TERRAIN CLEARANCE

PROJECTION TRANSVERSE MERCATOR  
 GRID INTERVAL 5000 YARDS  
 HORIZONTAL CONTROL DERIVED FROM TOPOGRAPHIC MAPS OBTAINED FROM STATE GOVERNMENT DEPARTMENTS, HOBART, TASMANIA

TOTAL MAGNETIC INTENSITY  
 AEROMAGNETIC SURVEY - S.W. TASMANIA  
 THE BROKEN HILL PROPRIETARY CO. LTD.



PLANS AND SPECIFICATIONS 1931-32  
 GEO SURVEY LTD, SYDNEY, AUSTRALIA

7218 32