



| LOCATION LAUNGESTON BASIN | | GAMMA RAY | | | |
|----------------------------|-----------------------------|--|-------|---|---|
| Company | GETTY OIL DEVELOPMENT | Initial Run | 2 | 3 | 4 |
| Project | | Logged Depth (ft) | 436 | | |
| Hole No. | V-8 Section | Range | 45/17 | | |
| County | State THS | Time Constant (sec) | 2 | | |
| Weather | | Paper Speed (ft/min) | 10 | | |
| HOLE DATA | | Logging Speed (ft/min) | 16 | | |
| Surface Elev | Date 6/1/73 | Bkgnd Count (cps) | 11 | | |
| Time | TD 440 Driller A. H. G. | Detector No | 12899 | | |
| Casing | NIL | Size (dia) (in) | 3 1/2 | | |
| Hole Size | 4 1/2" | ELECTRIC | | | |
| Bore Hole Medium | WATER Fluid Level 13' | Logged Depth (ft) | 436 | | |
| Start | 6/1/73 Completed 6/1/73 | Resist Scale (ohm/in) | 20 | | |
| Sampled Interval | 5' | S.P. Scale (mv/in) | 10 | | |
| INTERPRETATION DATA | | Paper Speed (ft/min) | 10 | | |
| Probe No. | 3026 Type SCINT Length 5' | Logging Speed (ft/min) | 16 | | |
| Standard (cps) | 5200 | Probe Size (in) | 1 3/8 | | |
| K Factor | .000040 | Type (w/d) | S.P. | | |
| Dead Time (used) | 10 | REMARKS REBASE S.P. AT 34', 73', 84', 90', & 165' | | | |
| Ratemeter No | 223 | REBASE P.R. AT 63', 6 100' | | | |
| Datum | G.L. Operator DUDLEY TOWERY | | | | |

