

Bore No.	Depth Metres		INTERVAL METRES	Pb ppm	W ppm	Bi ppm	Sn ppm	Mo ppm	Cu ppm	Zn ppm	Be ppm	CaF <sub>2</sub> %	Ag ppm	Au ppm	Remarks
	From	To													
SMD 7	41.00	42.00	1.0 metres	6	2300	560	840	55	42	120	30	24.5			SMD.7 ↓ X
7	42.00	43.00	1.0	4	540	460	720	24	60	100	40	25.0			
7	43.00	44.00	1.0	8	1850	340	540	160	35	120	40	19.0			
7	44.00	45.35	1.35	10	660	800	780	26	42	90	40	19.5			
7	45.35	46.15	0.8	12	180	410	1050	6	70	55	20	13.5			
7	46.15	47.30	1.15	10	370	520	980	12	32	90	30	13.5			
7	47.30	48.55	1.25	10	280	640	900	12	75	110	40	15.5			
7	48.55	50.00		20	3400	170	400	55	8	110	30	8.6			
7	50.00	51.00		20	840	42	380	180	8	120	20	5.9			
7	51.00	52.00		30	230	1300	490	14	10	70	50	10.0			
7	52.00	52.75		18	95	2050	420	8	28	85	80	15.0			
7	52.75	54.00		12	290	390	720	-4	18	95	80	16.0			
7	54.00	55.00		18	350	640	720	-4	25	110	80	22.0			
7	55.00	56.00		32	480	180	480	36	8	80	40	4.8			
7	56.00	57.00		28	760	28	420	170	8	75	80	5.3			
7	57.00	58.00		24	110	8	370	42	5	60	30	2.7			
7	58.00	59.00		12	270	12	390	24	8	75	80	3.9			
7	59.00	60.00		18	1200	8	600	140	8	85	80	9.5			
7	60.00	61.00		26	45	6	310	8	8	60	20	5.3			
7	61.00	62.00		26	80	-4	680		8	50	20	3.2			
7	62.00	63.00		26	150	8	740	4	8	70	30	4.4			
7	63.00	64.00		30	160	-4	1150	-4	8	65	30	2.9			
7	64.00	65.00		24	980	4	1000	12	8	65	30	4.0			
7	65.00	65.75		10	200	-4	330	160	5	100	30	7.8			
7	65.75	66.75		14	330	12	660	12	8	95	30	3.4			
7	66.75	67.75		12	480	32	380	42	25	60	20	6.8			
7	67.75	69.00		16	360	10	350	24	5	80	20	3.9			
7	69.00	70.00		-4	420	3	190	42	8	55	20	5.5			
7	70.00			8	270	-4	180	8	10	55	20	4.5			
DETECTION LIMIT				(4)	(10)	(4)	(4)	(4)			(1)		(1)	(0.05)	
METHOD OF ANALYSIS				X-RAY FLUORESCENCE SCHEME B1				CODE C1				CODE C2	CODE C3		

221501