ELECTROLYTIC ZINC CO OF A'ASIA LTD
ROSEBERY – TASMANIA

DIAMOND DRILL CORE RECORD

HOLE No. JCP 211

DEPTH (m) FROM	DEPTH (m) TO	ROCK DESCRIPTION	MINERALISATION
26.53	42.7	Gry-grn f g crystal tuff, felsic composition	
26.53	30.7	Zone: quartz veins with yellow oxidation haloes	
35.2	36.85	Zone of oxidation, yellow with Mn stained joint faces.	
36.85	42.7	Zone of fine irregular qtz & carbonate vning	
42.7	53.45	Reworked tuff; gry to gry-grn fg bedded, sorted siltstone/tuff, fine qtz veined.	T28369 Sericitic, mildly sheared pelitic sed; subaqueous tuff (51m)
51.2		Quartz carbonate veining	
53.2		" " "	
53.45	55.2	Gry-grn fg crystal vitric tuff, acid felsic composition, feldspar phenocrysts	
55.2	104.4	Lapilli tuff; dk gry with pink frags, coarse grained crystal, vitric tuff, acid-felsic composition. Sparse brecciated qtz-chl vns elongation of frags, pink felsic frags. containing qtz phenocrysts, siltstone frags and massive sulphide frags.	<1% pyrite T28370 (71.8,) altered & sheared rhyolitic tuff; flow or auto-brecciated ignimbrite
66		Large pink felsic, lithic frags.	
68.4	73.7	Agglomerate zone of pink felsic lithic frags	
73.7	84.2	Zone of crystal vitric tuff with fine felsic lithic fragments	
84.2	85.5	Zone of agglomerate: pink felsic lithic frags	
85.5	89.6	Zone of crystal vitric tuff with fine felsic with fine felsic frags & brecciated qtz carbonate veins	
89.6	104.4	Brecciated qtz carbonate vns dominant in crystal vitric tuff	pyrite in qtz carb veins.

SAMPLE NO.	FROM	TO	CORE REC'D	Sample Length	Pb	Zn	Cu	Ag - g/t	Au - g/t	Fe%	Mn	CORE REC'D RUN	CORE REC'D SHORT
28340	195	200		5.0	25	50	40	x			790	112.6	–
341	200	205		5.0	10	50	x	x			740	115.6	–
342	205	210		5.0	10	50	x	x			760	118.6	–
343	210	215		5.0	10	60	10	x			800	121.6	–
344	215	220		5.0	210	410	15	x			760	124.6	–
345	220	225		5.0	145	250	10	x			1000	127.6	–
346	225	230		5.0	10	55	10	x			950	130.6	–
347	230	235		5.0	10	60	x	x			750	133.6	–
348	235	240		5.0	15	80	x	x			900	136.6	–
349	240	245		5.0	15	60	x	x			700	139.6	–
28350	245	250		5.0	5	55	x	x			1000	142.6	–
351	250	255		5.0	10	55	x	x			950	145.6	–
352	255	260		5.0	5	55	x	x			950	148.6	–
353	260	265		5.0	270	790	10	x			730	151.6	–
												154.6	–
												157.6	–
28377	266	268		2.0	1050	2500	35	0.5			1600	160.6	–
379	268	270		2.0	385	740	35	x			1150	163.6	–
28380	270	272		2.0	370	590	55	x			1400	166.6	–
381	272	274		2.0	365	660	40	x			980	169.6	–
382	274	276		2.0	695	2000	30	x			855	172.6	–
383	276	278		2.0	1300	2700	20	x			730	175.6	–
384	278	280		2.0	60	155	25	x			870	178.6	–
385	280	282		2.0	2850	9500	30	2.0			900	181.6	–
386	282	284		2.0	850	2000	25	0.5			770	184.6	–
387	284	286		2.0	2000	4950	20	1.5			710	187.6	–
388	286	288		2.0	1950	4850	30	0.5			810	190.6	–
389	288	290		2.0	1150	3050	30	1.0			760	193.6	–
28390	290	292		2.0	190	320	30	x			735	196.6	–
391	292	294		2.0	45	280	30	x			590	199.6	–
392	294	296		2.0	175	475	45	x			850	202.6	–
393	296	298		2.0	430	1450	45	0.5			900	205.6	–
394	298	300		2.0	950	1800	90	1.5			1100	208.6	–
395	300	302		2.0	30	195	50	x			1050	211.6	–
396	302	304		2.0	15	215	15	x			1450	214.6	–
												217.6	–
28361	300	305		5.0	20	210	10	x			1600	220.6	–
362	305	310		5.0	85	190	45	x			1700	223.6	–
363	310	315		5.0	470	660	45	x			2000	226.6	–
364	315	320		5.0	195	530	20	x			2300	229.6	–
365	320	325		5.0	40	320	5	x			2650	232.6	–
366	325	330		5.0	30	150	x	x			570	235.6	–
367	330	335		5.0	25	100	x	x			1300	238.6	–
368	335	342.6		7.6	25	105	x	x			1500	241.6	–
												244.6	–
												247.6	–

058781