

All the reserve calculations are appended at the end of this report. The reserve blocks, referred to in the tables, are shown on the geological sections.

The calculated reserves are of a geological nature, and do not incorporate any mining criteria.

1. Dolomite Sulphide Lode Reserves

0.3% Sn Cut-off

Drill Indicated Ore Reserves	:	1,229,000 tonnes at 1.06% Sn
*Inferred Ore	:	70,000 tonnes at 1.05% Sn
Total	:	<u>1,299,000 tonnes at 1.06% Sn</u>
Contained tin	:	13,770 tonnes

\* Slaughteryard Face

2. Porphyry Reserves

0.2% Sn Cut-off

Drill Indicated Ore Reserves	:	2,486,000 tonnes at 0.46% Sn
Drill Inferred Ore	:	773,000 tonnes at 0.48% Sn
Total	:	<u>3,259,000 tonnes at 0.47% Sn</u>
Contained tin	:	15,320 tonnes

0.3% Sn Cut-off

Drill Indicated Ore Reserves	:	1,824,000 tonnes at 0.54% Sn
Drill Inferred Ore	:	609,000 tonnes at 0.55% Sn
Total	:	<u>2,433,000 tonnes at 0.54% Sn</u>
Contained tin	:	13,140 tonnes