

DRILL ADVANCE				LITHOLOGY							
LOST CORE	DEPTH	DRILL ADVANCE INTERVAL	CORE RECOVERY	PERCENT RECOVERY	INTERVAL	DESCRIPTION	ALTERATION	GRAPHIC LOG	STRUCTURE	MINERALISATION	VISUAL PERCENTAGE MINERALISATION
	0	1.0	0	0							
	1.0	3.4	3.4	100%	1-0	Tuffaceous sandstone coarse to medium grained grey-green with limonite staining. Clasts are poorly sorted but well bedded. Minor carbonaceous mudstone occurs as a matrix to rounded coarse lithics of tuffaceous sandstone. Minor grey to black shale interlayered units.	Limonite along fractures. Weathered rock.	1.0 45° in 0.2m of bk. sh. 1.3 10° F	Moderate fracturing. Units moderately to well-bedded.	Limonite after xaln Py Py 11.2	10%
	4.4	0.5	0.5	100%				4.8 50° B			
	4.9	0.5	0.5	100%				5.4 50° B			
	5.4	0.5	0.5	100%							
	5.9	1.0	1.0	100%							
	6.9	0.8	0.8	100%							
	7.7	1.5	1.0	66.6%			Unweathered except for limonite on fractures.	7.7 35° B			
	8.7	0.8	0.8	100%							
	9.5	0.4	0.4	100%	9.1	Mudstone gray to black, well bedded graded units with Py concentrated at base.	Minor weathering	9.7 40° B	grading indicates facing down hole.	fine grained Py in coarser units.	1%
	9.9	0.8	0.8	100%	9.9	Tuffaceous sandstone (as 1.0 to 9.1 m) with grey interbedded mudstone units, carbonaceous laminae and carbonaceous mudstone mixture.	Unweathered except for limonite on fractures.			Limonite in fractures after Py.	9.9
	10.7	1.0	1.0	100%							
	11.7	1.5	1.0	66.6%							
	13.2	1.2	0.65	54.1%	13.1	Black carbonaceous shale with minor interlayered units of coarse grained tuffaceous sandstone.	Soft and friable.		Well laminated.	Py altered in part to limonite	5%
	14.4	1.0	0.6	60%							

SCALE 1:100 (1cm = 1 m)

COMSTAFF PROPRIETARY LIMITED

DRILLHOLE LOG FOR DDH RBE 9

LOGGED BY G.E.P. FROM 0 TO 15

DATE / /

PAGE 3 OF 17