

	Matras	Sn	Cu	W	Pb	Zn	Ag	As									SAMPLE NUMBER
270																	
271	270-6	30	55	BLD	20	175	1.0	130								Split Core Recommendations	19040
272	271-75	290	260	BLD	25	185	1.5	2.6%									19041
273	272-75	350	3.7%	BLD	170	1100	59.5	1500									19042
274	273-75	2200	2.0%	BLD	220	700	42.5	180									19043
	274-3	1000	1.7%	BLD	60	370	29.5	180									19044
275	274-9	300	570	20	BLD	160	3.0	120									19045
276	275-9	100	155	BLD	20	215	0.5	12.0									19046
	276-55	65	2950	BLD	85	305	3.0	360									19047
277	277-0	65	360	BLD	70	285	1.0	2.2%								Split Core Finishes.	19048
278	277-5																
279		320	305	45	60	1900	1.5	5000									
280																	
281	280-5																
282		75	180	20	6300	3200	10.0	170									
283																	
284	283-5																
285		42	155	25	1350	4500	3.5	200									

COMSTAFF PROPRIETARY LIMITED

ASSAY RESULT SHEET FOR

DDH RBE 12

ASSAYED BY Analabs

FROM 270m TO 285m

DATE 22/9/80

PAGE 15 OF 17