

DRILL ADVANCE				LITHOLOGY						
DEPTH	DRILL ADVANCE INTERVAL	CORE RECOVERY	PERCENT RECOVERY	INTERVAL	DESCRIPTION	ALTERATION	GRAPHIC LOG	STRUCTURE	MINERALISATION	VISUAL PERCENTAGE MINERALISATION
15.0	1.2	1.2	100%					15.5 B 45°		
16.2	1.3	1.3	100%					16.7 B 35° pitted gy-gr sandstone after 1/2		
17.5	1.6	1.6	100%					17.0 B 40°		
19.1	1.5	1.5	100%					18.5 B 50°		
20.6	0.4	0.4	100%					19.7 B 40°		
21.0	1.1	1.1	100%					19.7 3mm weathered q.v. at 0°		
22.1	1.5	1.5	100%					21.4 B 60°		
23.6	1.8	1.8	100%					22.9 B 55°		
25.4	0.6	0.6	100%					24.2 5mm q.v. at 20° E associated weathered sulphide sites.		
26.0	1.0	1.1	100%					25.3 B 35°		
27.0	3.5	3.0	85.7%					26.8 B 30°		
								28.0 B 25°		
								28.8 haemiform Mn oxide along fracture at 25°.		

SCALE 1:100 (1cm = 1m)

COMSTAFF PROPRIETARY LIMITED

DRILLHOLE LOG FOR

DDH RBE 13

LOGGED BY N.P.G.

FROM 15 TO 30m

DATE 20/8/80

PAGE 3 OF 12