

APPENDIX G (Continued)

Line	Dipole Spacing	Plotting Point	Chargeability (mV/V)						Resistivity (ohm-m)						
			n=1	2	3	4	5	6	n=1	2	3	4	5	6	
144N	40 m	540 mE	4.2	-	-	-	-	-	1078	-	-	-	-	-	-
		520 mE	5.6	5.2	-	-	-	-	1287	1585	-	-	-	-	-
		500 mE	5.9	5.2	3.7	-	-	-	1158	2136	3854	-	-	-	-
		480 mE	4.8	4.3	3.1	2.5	-	-	1796	2531	5127	4343	-	-	-
		460 mE	5.2	3.4	3.1	2.0	2.2	-	1719	4138	3227	3228	2577	-	-
		440 mE	5.9	4.3	2.6	3.7	14.5	33.0	1448	2513	2850	2043	2628	2477	-
		420 mE	6.5	5.3	4.7	14.8	33.0	79.7	1258	1157	1910	2172	1979	980	-
		400 mE	5.6	6.4	16.0	31.5	79.0	66.0	1534	1095	945	1959	776	1027	-
		380 mE	7.0	14.5	32.2	76.5	64.5	55.5	4826	1157	900	356	844	1478	-
		360 mE	12.3	27.1	79.5	71.5	63.0	39.5	4105	1942	396	406	619	1140	-
		340 mE	22.0	81.0	71.3	61.5	53.2	24.5	1511	699	678	642	538	590	-
		320 mE	81.5	77.5	71.0	47.5	20.7	22.5	262	196	805	781	633	879	-
		300 mE	82.0	72.5	59.0	21.0	26.0	29.5	118	231	445	831	1282	1198	-
		280 mE	120.0	67.0	22.7	27.7	32.2	35.0	338	122	204	718	1660	1210	-
		260 mE	114.0	65.2	30.0	37.7	36.7	32.7	1521	173	207	449	744	1126	-
		240 mE	69.7	75.7	65.7	46.0	40.5	-	1530	1120	377	253	384	737	-
		220 mE	47.0	67.0	88.0	62.2	36.0	35.0	2853	3063	1116	297	240	597	-
		200 mE	39.0	55.7	72.7	89.2	63.0	39.5	5454	3706	1764	844	471	450	-
		180 mE	32.0	45.0	55.7	64.0	80.2	50.2	3808	3374	2557	2639	1473	569	-
		160 mE	32.5	31.0	44.2	56.0	67.5	85.0	5479	2230	4423	4549	1284	1121	-
		140 mE	35.0	24.5	28.0	40.0	60.0	-	3129	3194	3984	4841	3404	-	-
		120 mE	40.5	29.2	15.9	29.5	-	-	2760	4339	3100	2865	-	-	-
		100 mE	38.2	31.5	26.2	-	-	-	3061	2953	2915	-	-	-	-
		80 mE	34.5	34.5	-	-	-	-	1945	1579	-	-	-	-	-
60 mE	35.7	-	-	-	-	-	937	-	-	-	-	-	-		
120N	200 ft.	1600'W	12.5	-	-	-	-	-	4388	-	-	-	-	-	
		1700'W	13.1	10.0	-	-	-	-	7134	6844	-	-	-	-	
		1800'W	8.6	10.9	14.4	-	-	-	8073	7656	4833	-	-	-	
		1900'W	5.9	11.4	12.4	13.3	-	-	7810	3229	3982	4423	-	-	
		2000'W	9.3	7.6	9.7	12.0	14.5	-	3770	3671	3946	3851	5465	-	
		2100'W	9.2	8.6	6.5	10.3	13.8	27.7	2228	3267	3480	3325	4700	1716	
		2200'W	8.9	7.0	8.7	7.1	24.0	52.0	2460	3000	2987	2742	2960	1195	
		2300'W	9.4	8.1	7.1	19.5	48.7	63.0	1959	2900	2645	1749	1582	658	
		2400'W	9.5	9.1	17.8	44.5	54.5	46.7	1436	2026	2123	943	936	475	
		2500'W	6.9	17.1	45.0	57.7	49.5	44.5	1725	1225	818	557	635	611	
		2600'W	10.0	38.7	63.0	53.0	47.0	40.0	1663	631	260	324	861	647	
		2700'W	30.5	66.5	63.0	51.0	47.0	43.5	654	291	168	246	818	637	
		2800'W	67.0	72.0	64.5	56.5	56.7	39.0	299	133	232	282	1116	640	
		2900'W	74.0	76.0	68.5	54.5	45.0	46.0	167	236	186	258	475	397	
		3000'W	33.0	80.0	76.5	62.5	55.5	37.0	439	258	209	212	482	396	
		3100'W	9.6	42.7	87.0	75.0	52.5	47.5	565	464	271	216	267	478	
		3200'W	2.4	17.6	52.5	95.0	62.5	-	325	710	522	250	415	-	
3300'W	4.3	10.4	26.0	59.0	-	-	287	481	741	606	-	-			
3400'W	8.4	9.4	14.6	-	-	-	312	288	639	-	-	-			
3500'W	10.8	9.8	-	-	-	-	255	442	-	-	-	-			
3600'W	8.5	-	-	-	-	-	330	-	-	-	-	-			