

APPENDIX G (Continued)

Line	Dipole Spacing	Plotting Point	Chargeability (mV/V)						Resistivity (ohm-m)					
			n=1	2	3	4	5	6	n=1	2	3	4	5	6
40N	100 ft.	1300'W	-	10.7	-	20.0	-	-	-	1786	-	-	-	-
		1350'W	8.9	-	11.8	-	-	-	2088	-	2308	-	-	-
		1400'W	-	7.3	-	12.3	-	-	-	1183	-	2320	-	-
		1450'W	9.4	-	6.4	-	-	-	2227	-	1955	-	-	-
		1500'W	-	7.2	-	9.2	-	-	-	1594	-	3248	-	-
		1550'W	8.9	-	8.5	-	-	-	3687	-	2513	-	-	-
		1600'W	-	9.5	-	-	-	-	-	2088	-	-	-	-
		1650'W	11.1	-	-	-	-	-	3625	-	-	-	-	-
40N	200 ft.	1100'E	9.7	-	-	-	-	-	257	-	-	-	-	
		1000'E	8.4	11.1	-	-	-	-	406	598	-	-	-	
		900'E	10.0	14.9	18.7	-	-	-	713	618	755	-	-	
		800'E	19.5	14.8	13.2	20.0	-	-	959	693	475	734	-	
		700'E	25.5	12.2	16.5	-	-	-	870	538	278	-	-	
		600'E	28.0	16.3	10.5	-	-	-	816	710	536	415	-	
		500'E	34.5	20.5	6.5	9.2	-	-	870	1086	707	365	-	
		400'E	38.0	24.0	9.6	-	-	-	1718	955	769	385	-	
		300'E	28.0	27.5	21.0	-	-	-	1122	1189	738	882	-	
		200'E	21.0	21.0	22.0	16.5	-	-	758	1009	1227	891	-	
		100'E	13.6	20.0	21.0	20.0	-	-	740	858	1317	1293	-	
		00 B/L	10.5	13.0	14.9	17.2	-	-	1009	823	796	885	-	
		100'W	8.4	10.5	13.2	17.2	-	-	815	957	552	415	-	
		200'W	9.8	8.6	11.5	16.2	-	-	850	610	731	633	-	
		300'W	10.4	8.8	8.2	10.0	-	-	841	501	591	766	-	
		400'W	10.0	11.2	10.2	6.6	-	-	946	788	661	479	-	
		500'W	10.1	13.6	11.5	8.6	-	-	1352	1164	593	506	-	
		600'W	12.4	13.4	12.7	13.1	-	-	1211	992	783	889	-	
		700'W	16.2	13.2	14.4	16.8	-	-	645	738	1230	922	-	
		800'W	17.3	14.9	21.5	21.5	-	-	473	557	884	900	-	
		900'W	16.5	21.0	23.0	19.6	-	-	945	512	546	725	-	
		1000'W	19.3	26.5	28.0	20.0	-	-	791	707	426	452	-	
		1100'W	23.2	25.5	25.0	22.0	-	-	595	738	1000	464	-	
1200'W	20.0	23.7	24.2	23.2	-	-	1392	564	829	870	-			
1300'W	13.7	20.7	23.0	22.5	-	-	1461	1590	876	1288	-			
1400'W	8.6	16.4	21.0	21.7	-	-	1835	2598	2447	1180	-			
1500'W	7.9	11.2	16.4	20.0	-	-	1740	3071	3567	2669	-			
1600'W	8.7	8.1	12.0	17.7	-	-	1775	2668	3625	3568	-			
1700'W	8.3	7.8	9.5	13.2	-	-	1818	2157	2929	3116	-			
1800'W	8.4	7.9	8.5	-	-	-	1761	1891	2001	-	-			
1900'W	8.8	8.3	-	-	-	-	2126	1645	-	-	-			

Note: 1. Where stations were repeated the readings have been averaged.
 2. Chargeability is the middle slice of the Scintrex IPR-8 three-slice programme.