

APPENDIX J

Spicer Dipole-Dipole I.P. Data

Line	Dipole Spacing	Plotting Point	Chargeability (mV/V)						Resistivity (ohm-m)						
			n=1	2	3	4	5	6	n=1	2	3	4	5	6	
192S	40 m	2540 E	4.6	-	-	-	-	-	1646	-	-	-	-	-	-
		2520 E	4.9	5.2	-	-	-	-	1391	2420	-	-	-	-	-
		2500 E	6.2	5.2	4.0	-	-	-	2196	2488	2574	-	-	-	-
		2480 E	6.4	4.2	3.0	2.4	-	-	2545	2461	2443	2997	-	-	-
		2460 E	4.9	3.9	3.4	4.0	9.6	-	1689	2714	2941	2352	2196	-	-
		2440 E	3.7	3.6	5.6	11.0	8.9	6.6	1960	2606	2922	2419	1735	3223	-
		2420 E	5.1	5.6	10.9	10.6	8.6	6.4	2865	2300	2087	2149	3513	2273	-
		2400 E	5.9	11.6	11.6	9.7	6.6	6.1	2451	2654	1896	2780	2810	2343	-
		2380 E	10.7	13.1	11.1	7.9	8.8	14.2	2624	2168	3367	2297	1847	3694	-
		2360 E	13.1	12.3	9.7	10.0	13.1	14.0	2071	3004	2735	2319	2615	3842	-
		2340 E	14.2	11.8	11.3	14.8	13.4	7.9	2498	2256	2081	3374	4565	4145	-
		2320 E	17.6	12.9	15.4	14.6	10.7	7.7	1942	1674	3368	4283	5943	3212	-
		2300 E	18.3	21.2	18.5	11.5	10.6	8.2	1317	2239	3492	5554	3325	3209	-
		2280 E	14.4	23.9	16.4	9.3	10.4	9.6	2356	2522	3770	3152	2966	3293	-
		2260 E	16.5	13.4	17.3	16.5	11.5	12.7	4807	2473	2224	2454	2783	4011	-
		2240 E	12.3	9.4	11.8	17.5	17.4	13.6	3380	3784	2281	2187	2672	2812	-
		2220 E	15.3	9.2	10.0	15.4	21.0	17.0	1904	2066	3537	2341	2181	2639	-
		2200 E	20.5	13.9	11.0	14.3	16.7	19.6	2124	1787	2388	3304	2375	2533	-
		2180 E	16.7	23.0	16.8	12.5	10.0	9.7	2141	2460	1725	2420	3814	2217	-
		2160 E	15.8	20.5	23.5	12.8	3.7	5.1	2224	2171	2564	2013	2291	4238	-
2140 E	18.4	18.0	19.1	16.4	9.1	-	1508	2337	3230	2496	2246	-	-		
2120 E	21.0	16.5	10.7	14.1	-	-	1542	1785	2262	3510	-	-	-		
2100 E	21.5	12.7	10.3	-	-	-	2045	1484	1920	-	-	-	-		
2080 E	18.5	13.5	-	-	-	-	1495	1739	-	-	-	-	-		
2060 E	19.0	-	-	-	-	-	1860	-	-	-	-	-	-		

- Notes: 1. Surveyed by Scintrex Pty. Ltd. on 12th, 22nd and 23rd April, 1981.
2. Scintrex IPR-8 receiver. M_{32} slice of transient decay curve used for chargeability.
3. Where stations were repeated the values have been averaged.